



Nemo™ 1960 LED Light



The Nemo $^{\mathsf{TM}}$ 1960 LED brings the latest in LED technology to the dive market. Built compact and lightweight to fit inside your Buoyancy Compensator (BC) pocket yet bright enough to illuminate underwater exploration with 24 lumens. It is submersible to 100 meters and comes with a twist-on shroud. It's ABS resin body resists chemicals, corrosion, and extreme temperatures.



Nemo™ 1960 LED Light ANSI FL1 Specifications

Hiah		
LIGHT SOURCE.	LED	
BATTERIES	2 AAA Alkaline (Included)	
CHARGE TIME		
VOLTAGE	3	
LENGTH	13.9 cm (5.48")	
WEIGHT W/ BATTERIES	0.09 kg (3 oz.)	
WEIGHT W/O BATTERIES	0.03 kg (1.1 oz.)	


LIGHT OUTPUT

(hours/min)

BEAM DISTANCE (meters)

PEAK BEAM INTENSITY (candela)

WATERPROOF & SUBMERSIBLE



Materials

Lens	Snroud	Switch Type
Clear	Xenoy	Rotary Switch
Polycarbonate	 	Operation
		Night
Contact, Sprin & Retainer	g O- Ring	Vision
		NA
	Polycarbonate Contact, Sprin & Retainer	Clear Xenoy Polycarbonate Contact, Spring O-

Configuration

Cat. #	Description
1960N	Nemo™ 1960 LED Light
190014	Nemo 1900 LLD Light

Nemo™ 1960 LED Light Accessories

No accessories are currently available for this product