



## 2-1564544-1 Product Details



**2-1564544-1**

TE Internal Number: 2-1564544-1

Active

[View 3D PDF](#)

### Multiple Contact Point (MCP) & MCON Contact Systems

Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- HDSCS Product Line, Multiple Contact Point (MCP) Product Line
- Wire-to-Wire
- Applies To Wire/Cable
- Connector
- Housing

[View all Features](#)

#### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- [2POS. TAB 5.8x0.8 TAB HSG, ASSY 2pos. TAB 5.8x0.8 Fl...](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- [Heavy Duty Sealed Connector Series 2 to 18 positions...](#) (PDF, German)

#### Application Specifications:

- [Heavy Duty Sealed Connector Series \(HDSCS\) 2 to 18 p...](#) (PDF, English)

#### Instruction Sheets:

- None Available

#### CAD Files: (CAD Format & Compression Information)

- [2D Drawing](#) (DXF, Version H)
- [3D Model](#) (IGES, Version H)
- [3D Model](#) (STEP, Version H)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Product Line = HDSCS, Multiple Contact Point (MCP)
- Product Type = Connector
- Connector Type = Housing
- [Wire/Cable Type](#) = FLR (Thin Walled Cable)
- Key Type = Standard
- Sealed = Yes

#### Mechanical Attachment:

- Contact Retention = With
- Contact Retention Type = Secondary Locking/Retainer
- Mating Retention Type = Latching
- Panel Mount Retention = Without

#### Electrical Characteristics:

- Operating Voltage (VDC) = 42
- Operating Voltage Reference = DC

#### Termination Features:

- Termination Method to Wire/Cable = Crimp
- Seal Type = Radial Seal

#### Dimensions:

- Mating Area Interface Dimensions (mm [in]) = 6.3 [.248]

#### Body Features:

- Cable Exit Angle = 180°
- Mating Retention = With
- Wire Type = Stranded

#### Housing Features:

- Connector Style = Plug
- Housing Material = PBT - GF30
- Housing Color = Gray
- Mating Alignment = With
- Mating Alignment Type = Keyed

#### Configuration Features:

- Number of Positions = 2
- Number of Rows = 1
- Strain Relief = Without

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- UL Flammability Rating = UL 94V-0

#### Identification Marking:

- Keying = B

#### Environmental:

- Operating Temperature (°C [°F]) = -40 - +140 [-40 - +284]

#### Conditions for Usage:

- Applies To = Wire/Cable

#### Operation/Application:

- Application Use = Wire-to-Wire

- Seal Material = Silicone
- Seal Color = White
- Used With = Receptacle Housing

**Contact Features:**

- Contact Type = Tab

**Packaging Features:**

- Packaging Method = Box/Carton
- Packaging Quantity = 320

**Other:**

- Brand = TE Connectivity
- Comment = IP67 and IP69K

**Corporate Information**

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

**Quick Links**

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

**Customer Support**

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

**Keep Me Informed**

