




2-1734346-3 Product Details

[Share](#)[Print](#)[Email](#)**2-1734346-3**

TE Internal Number: 2-1734346-3



Active

[View 3D PDF](#)

Universal Serial Bus (USB) Connectors



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- USB 2.0 Industry Standard
- Size = Standard
- B Series
- Receptacle
- Without Locking Feature

[View all Features](#)**Quick Links**

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)[Request Sample](#)[Find Similar Products](#)[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [USB CONNECTOR, SERIES B, 4 POSITIONS, R/A, SMT TYPE,...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- [2D Drawing](#) (DXF, Version C)
- [3D Model](#) (IGES, Version C)
- [3D Model](#) (STEP, Version C)

[List all Documents](#)**Related Products:**

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Size = Standard
- Gender = Receptacle
- Orientation = Right Angle
- LED = Without
- PCB Mount Retention Type = SMT Hold Down

Mechanical Attachment:

- Mount Location = Top

Termination Features:

- Contact Termination Type = Surface Mount
- Termination Method = Solder

Body Features:

- Locking Feature = Without
- [Panel Ground](#) = Without
- Shell Plating = Nickel over Copper
- Assembly Process Feature = Without Pick and Place Cover
- Locating Post(s) = With

Contact Features:

- [Contact Plating](#), [Mating Area](#), [Material](#) = Gold Flash

Housing Features:

- [Housing Color](#) = Black

Configuration Features:

- Number of Ports = 1
- Number of Positions = 4

Industry Standards:

- Industry Standard = USB 2.0
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- USB-IF Test ID Number (TID) = Not Submitted For Testing

Conditions for Usage:

- Applies To = Printed Circuit Board

Packaging Features:

- [Packaging Method](#) = Tape & Reel

Other:

- [Series](#) = B
- Brand = AMP

About TE
Investors
News Room
Supplier Portal
Careers
Terms & Conditions
Privacy Policy
AODA Accessibility Policy
AODA Multi-Year Accessibility
Plan

Distributor Inventory
Product Cross Reference
Documents & Drawings
Product Compliance Support Center
Site Map

Email or Chat With Us
Find a Phone Number
Knowledge Base
Manage Your Account

