



CRIMP RINGS & SPADES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

TERMINAL,PIDG R SLTD 26-22 6

PIDG | PIDG

2-323011-2

TE Internal Number: 2-323011-2

Always EU RoHS/ELV Compliant

Terminal Shape **Ring Tongue**

Stud Diameter **3.68 mm [.145 in]**

Tongue Thickness **.5 mm [.0197 in]**

Sealed **No**

Heavy Duty **No**

Product Drawings

WIRE TERMINAL P.I.D.G SLOTTED RING TONGUE WIRE SIZE 26-22

PDF
English

CAD Files

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

| | |
|------------------------|---------------------------|
| Sealed | No |
| Barrel Type | Closed Barrel |
| Wire/Cable Type | Regular Wire |
| Insulated | Yes |
| Insulated Wire Support | Yes |
| Support Style | Insulation Support |
| Stud Size | 6, M3.5 |
| Shape Code | Slotted Ring-001 |

| | | |
|----------------------------|--------------------------------|---|
| | Terminal Features | Slotted |
| | Wire/Cable Composition | Solid or Stranded |
| Configuration Features | Terminal Angle | Straight |
| Electrical Characteristics | Voltage (Max) (V) | 300 |
| Body Features | Plating Material | Copper, Tin |
| | Insulation Sleeve Material | Copper |
| | Insulation Sleeve Color | Yellow |
| | Insulation Material | Nylon |
| | Inspection Slot | No |
| | Weight per Piece (g) | .294 |
| | Insulation Type | Pre-Insulated |
| Contact Features | Terminal Shape | Ring Tongue |
| | Terminal Orientation | Straight |
| Dimensions | Stud Diameter | 3.68 mm [.145 in] |
| | Tongue Thickness | .5 mm [.0197 in] |
| | Wire Insulation Diameter (Max) | 2.08 mm [.082 in] |
| | Wire Insulation Diameter | 1.27 – 2.08 mm [.05 – .082 in] |
| | Wire Size (AWG) | 26 – 22 |
| | Wire Size (mm ²) | .1 – .41 |
| | Wire Size (CMA) | 202 – 810 |
| | Overall Length | 18.26 mm [.7189 in] |
| Operation/Application | Heavy Duty | No |
| Industry Standards | Government Qualified | No |
| Packaging Features | Packaging Method | Tape Mounted |
| | Packaging Quantity | 1000 |
| Other | Barrel Color | Yellow |

CUSTOMERS ALSO BOUGHT

| HOOK UP WIRE | RECTANGULAR POWER CONNECTORS | CRIMP RINGS & SPADES | RECTANGULAR POWER CONNECTORS |
|---|---|---|---|
| 22759/32-30-0 22759/32-30-0 | PLUG HSG, AMPINNERGY WTB, 3 POS 556879-3 | PIDG SPD 22-16 COMM 22-18MIL 8 2-32053-1 | 05P MTA156 HDR ASSY SQ STR F/L 644752-5 |
| Save to List Find Similar Products |