

CATALOG

Cross Reference

[Competitive Products](#)
[Military Spec P/Ns](#)
[Tyco Brand P/Ns](#)

- ➔ [Part Number Search](#)
- ➔ [Document Search](#)
- ➔ [Product Type Search](#)
- ➔ [Product Family Search](#)
- ➔ [Alphabetical Search](#)
- ➔ [RoHS/ELV Compliance & Alternates](#)
- ➔ [CAD Model Search](#)
- ➔ [Brand Search](#)
- ➔ [Tool Search](#)
- ➔ [Multiple Part Comparison](#)
- ➔ [Lead Free Solutions](#)
- ➔ [Help/Glossary](#)

[Home](#)

e-bulletin newsletter
SUBSCRIBE NOW!
click here

Sockets

➔ DIP Sockets

AMP **2-641604-4**  [Active](#)

(Corporate P/N: 2-641604-4)

[Not ELV or RoHS Compliant](#)

[Search for Compliant \(RoHS/ELV\)](#)

[Alternates](#)

[CAD Geometry](#) | [Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
➤ General Info ➤ Sales Info ➤ Assembly Subcontractors	➤ Pricing & Availability	➤ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:

Brand:	AMP
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Wave solder capable to 240°C
Product Type:	DIP Socket
Number of Positions:	24
Row-to-Row Spacing (mm [in]):	15.49 [0.610]
Contact Mount:	Thru Hole
Mount Style:	Vertical
Centerline (mm [in]):	2.54 [0.100]
Profile:	Standard
Frame Style:	Ladder

Other Properties:

Proprietary Name:	DIPLOMATE DL
Insulation Resistance (M•):	10,000
Contact Resistance (m •):	30
Color:	Black
Housing Material:	Glass-Filled Thermoplastic
Housing Flammability Rating:	UL 94V-0
Application:	Production
Qty./Tube:	17
Contact Termination Area Plating:	Tin-Lead
Qty. Tubes/Box:	100
Product Series:	Standard

<u>Leg Style:</u>	Straight
<u>Contact Material:</u>	Phosphor Bronze
<u>Contact Mating Area Plating:</u>	Gold (15)
<u>Contact Style:</u>	Stamped + Formed
<u>Mating Contact Type:</u>	Dual Leaf
<u>Height Above PC Board (mm [in]):</u>	5.33 [0.210]
<u>Temperature Range (°C):</u>	125
<u>Packaging Method:</u>	Tube
<u>Termination Post Length (mm [in]):</u>	3.25 [0.128]

Comment:	ONLY sockets with straight solder tails are recommended for automatic insertion.
-----------------	--

[Copyright](#) and [Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]