Restricted to: General Release

USED ON



Left Side

Connector(s): MPO SECURE (No Pins)
Mode: MM
Housing Color: Green
Geom. Spec: N/A

Right Side

Connector(s): MPO SECURE (No Pins)
Mode: MM
Housing Color: Green
Geom. Spec: N/A

Notes:

1 IL tested at 1300nm.
2 Product and Processing must meet requirements of Tyco Electronics Standard 230-702
3 A copy of test data will be placed inside or with the unit package.
4 Label 2 will not be present on any cable assembly less than 5 meters long.
5 The cable meets or exceeds the requirements of GR-409-CORE for both RISER and PLENUM applications.
6 The cable meets or exceeds the UL requirements for both RISER and PLENUM applications.

P	LTR	REVISION RECORD	DATE	DWN	APVD
	A	Rev Per EC# RELEASE	0/13/2006	-	MK

DIMENSIONS: meters
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - ; 1 PLC ± - ; 2 PLC ± - ; 3 PLC ± - ; 4 PLC ± -
Customer Print

DWN: Cable Assy Configurator
CHK: Michael Kepko
APVD: Michael Kepko
MATERIAL: -
HEAT TREAT: -
AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608
NAME: FO C/A - 24 fiber, 50/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)
SCALE: NTS | SIZE: A2 | DRAWING NO: C- 6754282 | SHEET: 1 of 5 | REV: A

LOC CE
DIST 16

CAC Customer Layout Rev: D

THIS DRAWING IS A CONTROLLED DOCUMENT
DWG NO 6754282
THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES, AND MAY NOT BE COPIED, REPRODUCED, USED, DISCLOSED, OR DISTRIBUTED BY TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

Restricted to: General Release

USED ON

THIS DRAWING IS A CONTROLLED DOCUMENT.
DWG NO



View A-A
Not to Scale

Pairs Flipped

A-A Fiber Color	Connector Position #	B-B Fiber Color
Blue	1	Orange
Orange	2	Blue
Green	3	Brown
Brown	4	Green
Slate	5	White
White	6	Slate
Red	7	Black
Black	8	Red
Yellow	9	Violet
Violet	10	Yellow
Rose	11	Aqua
Aqua	12	Rose



View B-B
Not to Scale

Lightray Connector Fiber Path

Leg 1 —— 1 Leg
Leg 2 —— 2 Leg

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES, AND IS NOT TO BE DISCLOSED TO ANY OTHER PERSON OR COMPANY WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION. ALL RIGHTS OF TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

P	LTR	REVISION RECORD	DATE	DWN	APVD
A		Rev Per EC# RELEASE	0/13/2006	-	MK

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -

Customer Print

DWN: Cable Assy Configurator
CHK: Michael Kepko
APVD: Michael Kepko
MATERIAL: -
HEAT TREAT: -

AMP Tyco Electronics, Inc.
Harrisburg, PA 17105-3608

NAME: FO C/A - 24 fiber, 50/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)

SCALE	SIZE	DRAWING NO	SHEET	REV
NTS	A2	C- 6754282	2 of 5	A

LOC CE
DIST 16

CAC Customer Layout Rev: D

8 7 6 5 4 3 2 1

D C B A

Restricted to: General Release

USED ON

Part #	L (meters)	L (feet)	MPO SECURE (No Pins), Green IL (dB)	MPO SECURE (No Pins), Green RL (dB)	MPO SECURE (No Pins), Green IL (dB)	MPO SECURE (No Pins), Green RL (dB)
0-6754282-1	3.048 - 3.353	10.00 - 11.00	0.75	-	0.75	-
0-6754282-2	6.096 - 6.706	20.00 - 22.00	0.76	-	0.76	-
0-6754282-3	9.144 - 9.754	30.00 - 32.00	0.76	-	0.76	-
0-6754282-4	12.192 - 12.802	40.00 - 42.00	0.77	-	0.77	-
0-6754282-5	15.240 - 15.850	50.00 - 52.00	0.77	-	0.77	-
0-6754282-6	18.288 - 18.898	60.00 - 62.00	0.78	-	0.78	-
0-6754282-7	21.336 - 21.946	70.00 - 72.00	0.78	-	0.78	-
0-6754282-8	24.384 - 24.994	80.00 - 82.00	0.79	-	0.79	-
0-6754282-9	27.432 - 28.042	90.00 - 92.00	0.79	-	0.79	-
1-6754282-0	30.480 - 31.394	100.00 - 103.00	0.8	-	0.8	-
1-6754282-1	33.528 - 34.442	110.00 - 113.00	0.8	-	0.8	-
1-6754282-2	36.576 - 37.490	120.00 - 123.00	0.8	-	0.8	-
1-6754282-3	39.624 - 40.538	130.00 - 133.00	0.81	-	0.81	-
1-6754282-4	42.672 - 43.586	140.00 - 143.00	0.81	-	0.81	-
1-6754282-5	45.720 - 46.634	150.00 - 153.00	0.82	-	0.82	-
1-6754282-6	48.768 - 49.682	160.00 - 163.00	0.82	-	0.82	-
1-6754282-7	51.816 - 52.730	170.00 - 173.00	0.83	-	0.83	-
1-6754282-8	54.864 - 55.778	180.00 - 183.00	0.83	-	0.83	-
1-6754282-9	57.912 - 58.826	190.00 - 193.00	0.84	-	0.84	-
2-6754282-0	60.960 - 62.179	200.00 - 204.00	0.84	-	0.84	-
2-6754282-1	64.008 - 65.227	210.00 - 214.00	0.85	-	0.85	-
2-6754282-2	67.056 - 68.275	220.00 - 224.00	0.85	-	0.85	-
2-6754282-3	70.104 - 71.323	230.00 - 234.00	0.86	-	0.86	-
2-6754282-4	73.152 - 74.371	240.00 - 244.00	0.86	-	0.86	-
2-6754282-5	76.200 - 77.419	250.00 - 254.00	0.86	-	0.86	-
2-6754282-6	79.248 - 80.467	260.00 - 264.00	0.87	-	0.87	-
2-6754282-7	82.296 - 83.515	270.00 - 274.00	0.87	-	0.87	-
2-6754282-8	85.344 - 86.563	280.00 - 284.00	0.88	-	0.88	-
2-6754282-9	88.392 - 89.611	290.00 - 294.00	0.88	-	0.88	-
3-6754282-0	91.440 - 93.269	300.00 - 306.00	0.89	-	0.89	-
3-6754282-1	94.488 - 96.378	310.00 - 316.20	0.89	-	0.89	-
3-6754282-2	97.536 - 99.487	320.00 - 326.40	0.9	-	0.9	-
3-6754282-3	100.584 - 102.596	330.00 - 336.60	0.9	-	0.9	-
3-6754282-4	103.632 - 105.705	340.00 - 346.80	0.91	-	0.91	-
3-6754282-5	106.680 - 108.814	350.00 - 357.00	0.91	-	0.91	-
3-6754282-6	109.728 - 111.923	360.00 - 367.20	0.91	-	0.91	-
3-6754282-7	112.776 - 115.032	370.00 - 377.40	0.92	-	0.92	-
3-6754282-8	115.824 - 118.140	380.00 - 387.60	0.92	-	0.92	-
3-6754282-9	118.872 - 121.249	390.00 - 397.80	0.93	-	0.93	-
4-6754282-0	121.920 - 124.358	400.00 - 408.00	0.93	-	0.93	-
4-6754282-1	124.968 - 127.467	410.00 - 418.20	0.94	-	0.94	-
4-6754282-2	128.016 - 130.576	420.00 - 428.40	0.94	-	0.94	-
4-6754282-3	131.064 - 133.685	430.00 - 438.60	0.95	-	0.95	-
4-6754282-4	134.112 - 136.794	440.00 - 448.80	0.95	-	0.95	-

Qty	U of M	Description	Item No.
0.167	piece	Label, 1 & 2	23
3	piece	Trace Label	22
4	piece	Ferrule, MT, MM, 12 Fiber	21
0.2	RL	Electrical Tape	20
4.06	meters	Oval Tube, Orange	19
4	piece	Boot, MPO - Green	18
4	piece	Dust Cover	17
1	piece	Braided Sleeve	16
1	piece	Caution Label	15
1	piece	Pulling Sock	14
4	piece	Spirap 5.5"	13
1	piece	Heat Shrink Tubing	12
0.5	piece	Foam Cap	11
4	piece	Construction tape	10
2	piece	Heat Shrink Tubing	9
4	piece	Crimp Ring	8
4	piece	Spring Retainer	7
4	piece	Spring	6
4	piece	Connector Housing	5
AR	meter	24 Fiber, 50/125, 7.8mm, CLT, Orange, OFNR/OFNP	4
2	piece	VACUUM HOSE, SPIRAFLEX 1 FOOT	3
4	piece	Pin Holder w/out Pins	2
4	piece	Mini boot, 12 fiber	1

THIS DRAWING IS A CONTROLLED DOCUMENT.
DWG NO

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "TYCO"). IT IS TO BE USED ONLY FOR THE BENEFIT OF TYCO ELECTRONICS PERSONNEL, AND MAY NOT BE DISCLOSED TO OTHERS WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA 17105-3608, USA.

LOC	DIST
CE	16

CAC Customer Layout Rev: D

P	LTR	REVISION RECORD	DATE	DWN	APVD
A		Rev Per EC# RELEASE	0/13/2006	-	MK

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -

Customer Print

DWN: Cable Assy Configurator
CHK: Michael Kepko
APVD: Michael Kepko
MATERIAL: -
HEAT TREAT: -

Tyco Electronics, Inc.
Harrisburg, PA 17105-3608

NAME: FO C/A - 24 fiber, 50/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)

SCALE	SIZE	DRAWING NO	SHEET	REV
NTS	A2	C- 6754282	3 of 5	A

8 7 6 5 4 3 2 1

D C B A

Restricted to: General Release

USED ON

Part #	L (meters)	L (feet)	MPO SECURE (No Pins), Green IL (dB)	MPO SECURE (No Pins), Green RL (dB)	MPO SECURE (No Pins), Green IL (dB)	MPO SECURE (No Pins), Green RL (dB)
4-6754282-5	137.160 - 139.903	450.00 - 459.00	0.96	-	0.96	-
4-6754282-6	140.208 - 143.012	460.00 - 469.20	0.96	-	0.96	-
4-6754282-7	143.256 - 146.121	470.00 - 479.40	0.96	-	0.96	-
4-6754282-8	146.304 - 149.230	480.00 - 489.60	0.97	-	0.97	-
4-6754282-9	149.352 - 152.339	490.00 - 499.80	0.97	-	0.97	-
5-6754282-0	152.400 - 155.448	500.00 - 510.00	0.98	-	0.98	-
5-6754282-1	160.020 - 163.220	525.00 - 535.50	0.99	-	0.99	-
5-6754282-2	167.640 - 170.993	550.00 - 561.00	1	-	1	-
5-6754282-3	175.260 - 178.765	575.00 - 586.50	1.01	-	1.01	-
5-6754282-4	182.880 - 186.538	600.00 - 612.00	1.02	-	1.02	-
5-6754282-5	190.500 - 194.310	625.00 - 637.50	1.04	-	1.04	-
5-6754282-6	198.120 - 202.082	650.00 - 663.00	1.05	-	1.05	-
5-6754282-7	205.740 - 209.855	675.00 - 688.50	1.06	-	1.06	-
5-6754282-8	213.360 - 217.627	700.00 - 714.00	1.07	-	1.07	-
5-6754282-9	220.980 - 225.400	725.00 - 739.50	1.08	-	1.08	-
6-6754282-0	228.600 - 233.172	750.00 - 765.00	1.09	-	1.09	-
6-6754282-1	236.220 - 240.944	775.00 - 790.50	1.1	-	1.1	-
6-6754282-2	243.840 - 248.717	800.00 - 816.00	1.12	-	1.12	-
6-6754282-3	251.460 - 256.489	825.00 - 841.50	1.13	-	1.13	-
6-6754282-4	259.080 - 264.262	850.00 - 867.00	1.14	-	1.14	-
6-6754282-5	266.700 - 272.034	875.00 - 892.50	1.15	-	1.15	-
6-6754282-6	274.320 - 279.806	900.00 - 918.00	1.16	-	1.16	-
6-6754282-7	281.940 - 287.579	925.00 - 943.50	1.17	-	1.17	-
6-6754282-8	289.560 - 295.351	950.00 - 969.00	1.18	-	1.18	-
6-6754282-9	297.180 - 303.124	975.00 - 994.50	1.2	-	1.2	-
7-6754282-0	304.800 - 310.896	1000.00 - 1020.00	1.21	-	1.21	-

THIS DRAWING IS A CONTROLLED DOCUMENT.
DWG NO
THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES, AND IS FURNISHED SUBJECT TO AN EXISTING CONFIDENTIALITY AGREEMENT OR NON-DISCLOSURE AGREEMENT WITH TYCO ELECTRONICS. IT MAY NOT BE DISCLOSED, REPRODUCED OR USED IN WHOLE OR IN PART WITHOUT THE WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

LOC	DIST
CE	16

CAC Customer Layout Rev: D

P	LTR	REVISION RECORD	DATE	DWN	APVD
A		Rev Per EC# RELEASE	0/13/2006	-	MK

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ±

Customer Print

DWN: Cable Assy Configurator
CHK: Michael Kepko
APVD: Michael Kepko

MATERIAL: -
HEAT TREAT: -

AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608

NAME: FO C/A - 24 fiber, 50/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)

SCALE	SIZE	DRAWING NO	SHEET	REV
NTS	A2	C- 6754282	4 of 5	A

8 7 6 5 4 3 2 1

D C B A

Restricted to: General Release

USED ON

Label 1 Per specification 107-1645-1



This label is used on all lengths on this drawing.

Label 2 Per specification 107-1645-1



This label is used on all lengths on this drawing.



Protective Cover
Bottom End



Pulling Sock
Top End

THIS DRAWING IS A CONTROLLED DOCUMENT.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES, AND IS NOT TO BE DISCLOSED TO ANY OTHER PARTY, USED FOR ANY OTHER PURPOSE, OR REPRODUCED IN ANY MANNER WHATSOEVER WITHOUT THE PRIOR WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA

LOC	DIST
CE	16

CAC Customer Layout Rev: D

P	LTR	REVISION RECORD	DATE	DWN	APVD
A		Rev Per EC# RELEASE	0/13/2006	-	MK

DIMENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -

Customer Print

DWN: Cable Assy Configurator	MATERIAL: -	HEAT TREAT: -	
CHK: Michael Kepko			
APVD: Michael Kepko	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608		
NAME: FO C/A - 24 fiber, 50/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)			
SCALE: NTS	SIZE: A2	DRAWING NO: C- 6754282	SHEET: 5 of 5 REV: A

8 7 6 5 4 3 2 1

D C B A