



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)
35P TAB HSG
AMP | Timer Connector System

2-825213-5
TE Internal Number: 2-825213-5

Always EU RoHS/ELV Compliant

Tab Width **3 mm [.118 in]**

Tab Thickness **.8 mm [.031 in]**

Pitch **5 mm [.197 in]**

Number of Circuits **35**

Sealed **No**

Product Drawings

[35 Pol. Messerleiste](#)
PDF (TIFF AVAILABLE)
English

[35 Pol. Messerleiste](#)
PDF (TIFF AVAILABLE)
English

CAD Files

[Customer View Model](#)
2D_DXF.ZIP
English

[Customer View Model](#)
3D_IGS.ZIP
English

[Customer View Model](#)
3D_STP.ZIP
English

[3D PDF](#)
PDF
English

Product Specifications

Product Specification

[Packaging Instruction](#)
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sealed **No**

Hybrid Header **No**

Shielded **No**

Configuration Features	Number of Circuits	35
	Number of Rows	2
	Number of Sections	1
	Number of Signal Positions	35
Body Features	Color	Black
Contact Features	Tab Width	3 mm [.118 in]
	Tab Thickness	.8 mm [.031 in]
	Circuit Application	Signal
	Interface Plating	Tin (Sn)
Termination Features	Termination Method	Through Hole - Solder
Mechanical Attachment	Mounting Orientation	Horizontal/90°
	PCB Mount Retention Type	Mounting Holes
	PCB Mount Retention	With
	Panel Mount Retention	Without
	Mounting Holes	With
	PCB Mount Alignment	Without
	Locking Interface	Without
Housing Features	Pitch	5 mm [.197 in]
Dimensions	Profile Height from PCB	17.7 mm [.697 in]
	Width	25 mm [.984 in]
	PCB Thickness (Recommended)	1.6 mm [.062 in]
	Length	114 mm [4.488 in]
Industry Standards	UL Flammability Rating	UL 94-HB
Packaging Features	Packaging Type	Loose Piece
	Packaging Quantity	176

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

[VIEW ALL PRODUCT COMPLIANCE](#)