



Grey Halogen-Free Narrow Slot Betaduct is manufactured in the UK from Noryl NH5110E. It provides a lightweight self-extinguishing cable trunking with excellent rigidity and performance characteristics. Ideal for use with slimmer terminal blocks where more access is required, it improves appearance of panels with cables out in best position. For use when bundles, cables and wires need supporting in control panels, distribution boards and switchgear. Ideal for use in applications where danger to members of the public is a concern such as public buildings, shopping centre's, hospitals, airport terminals, stadiums, as well as a variety of hostile environments.

Available in 15 sizes. Recommended fixing method; Betaduct rivets or washers. [Supplied with lid.](#)

SPECIFICATIONS

MATERIAL:

Halogen-Free Noryl NH5110E

SLOT PITCH: 10mm **SLOT WIDTH:** 4mm **WEBS:** 6mm

COLOUR:

Light Grey RAL 7035

SERVICE TEMPERATURE RATING:

-25°C to +90°C

OXYGEN INDEX:

35.7% BS EN ISO 4589-2: 1999

SMOKE TEST:

BS 6853: 1999 Annex D.8.3
(Small scale smoke emission test).

FLAMMABILITY:

UL94 V-1 Rated Material

STANDARDS:

cULus and UL Approved.

PART NO. GREY	NOMINAL SIZE INNER (WxH) mm	NOMINAL SIZE OUTER (WxH) mm	PACK QTY (m)
20470022	25 x 37.5	29 x 41	24
20470023	25 x 50	29 x 54	24
20470024	25 x 75	29 x 79	16
20470032	37.5 x 37.5	41 x 41	24
20470033	37.5 x 50	41 x 54	16
20470034	37.5 x 75	41 x 79	16
20470035	37.5 x 100	41 x 105	16
20470053	50 x 50	54 x 54	16
20470054	50 x 75	55 x 79	16
20470055	50 x 100	56 x 105	8
20470073	75 x 50	78 x 54	16
20470074	75 x 75	80 x 80	16
20470075	75 x 100	80 x 105	8
20470103	100 x 50	107 x 54	8
20470104	100 x 75	107 x 80	8
20470105	100 x 100	107 x 104	8

