

LC CONN. MARK		LC CONN. MARK
A	↔	B
B	↔	A

NOTES:

- 1
- ATTENUATION ≤ 0.3 dB, MEASURED AT 850 nm
ACCORDING TO I.E.C. 61300-3-4 INSERTION METHOD B
- 2
- RETURN LOSS ≥ 25 dB, IN MATED CONDITION
AGAINST REFERENCE CONNECTOR AT 850 nm
- 3
- TEST RESULT SHEET IS SUPPLIED WITH EACH INDIVIDUAL PACKED ASSEMBLY
- 4
- CABLE INFORMATION:

— CORE DIAMETER:

50/125 μm

— OUTER JACKET DIAMETER:

1.8x3.6 mm

— OUTER JACKET COLOUR:


AQUA

— OUTER JACKET MATERIAL:

LSZH

5 BLANK LABEL

STANDARD LENGTHS ACCORDING TO CUSTOMER DRAWING 1206850	
PART NUMBER	"L" (meter)
X-2061311-Y	XY.0

2	BLANK LABEL			3
2	LC DUPLEX CONNECTOR, MULTI MODE, BEIGE			2
L	FOCAB 1.8MZ 50/125 OM3, AQUA, LSZH			1
Qty	Description			Item
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. COOLEN 16OCT2009 CHK A. HENGELMOLEN 16OCT2009 APVD A. HENGELMOLEN 16OCT2009 PRODUCT SPEC — APPLICATION SPEC — WEIGHT —	Tyco Electronics Corporation 's-Hertogenbosch, Nederland FIBER OPTIC LEAD 1.8MZ LC/DPX – LC/DPX MULTI MODE 50/125 OM3	
DIMENSIONS: mm		NAME		
		SIZE A2		
MATERIAL —		CAGE CODE 00779		
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± - FINISH —		DRAWING NO C=2061311		
CUSTOMER DRAWING		RESTRICTED TO —		
SCALE NTS		SHEET 1 of 1		
REV A				