


2110A, 2111A, 2112A, 2113A and 2195A Series Non-Relampable Neon-Incandescent Indicator Lights

Description and Features



Mounting: Ø.310 MIN., supplied with push-on speednut SN1287.

Wire Leads: No. 22 AWG (105°C) 4.40/4.80 long, stripped .430/.570

Lens: Polycarbonate-neon transparent, incandescent-translucent

Bezel: White nylon.

Housing: White Nylon

Lens Color	Neon		Incandescent	
	Model No. (105-125VAC)	Model No. (208-250VAC)	Model No. (12V)	Model No. (28V)
Red	2110A1	2111A1	2195A1-12V	2195A1-28V
Clear	2110A2	2111A2	-	-
Amber	2110A3	2111A3	2195A3-12V	2195A3-28V
White	2110A4	-	-	-
Green	2112A5*	2113A5*	2195A5-12V	2195A5-28V
Blue	2112A6**	2113A6**	-	-
Lamp used	C 2A+Resistor	C 2A+Resistor	#2162	#2187
Lead Color	Black	Black/Red	Yellow	Purple
"A" DIM	1.480	1.480	.740	.740

* Incorporates G2B lamp and resistor.

** Incorporates T2B lamp and resistor.

Underwriters Laboratories (UL) File No. E20356

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

VCC:

[2111A4](#) [2195A1-12V](#) [2195A3-12V](#) [2195A4-12V](#) [2195A4-28V](#) [2195AX1-12V](#) [2195AX3-12V](#) [2195AX1-28V](#)
[2195AX3-28V](#) [2195AX4-12V](#) [2195AX4-28V](#) [2195AX5-12V](#) [2195AX5-28V](#) [2110AX1](#) [2110AX2](#) [2110AX4](#) [2111AX1](#)
[2111AX2](#) [2111AX4](#) [2195A3-6V](#) [2195A4-6V](#) [2195A1-6V](#) [2195A5-6V](#)