

## Pneumatic connection technologies ▶ Push-In fittings

### Series QR1-S standard

▶ Angled plug connector ▶ push-in fitting ▶ Ø 4 - Ø16 ▶ push-in fitting ▶ Ø 4 - Ø16 ▶ QR1-S-RVK



00117304

Ambient temperature min./max.  
Working pressure min./max.

+32°F / +140°F  
-13 psi / 145 psi

**Materials:**


Screw  
Housing  
Seal  
Tooth lock washer  
Release ring  
Release ring holder

nickel-plated  
Polybutyleneterephthalate  
Acrylonitrile Butadiene Rubber  
Stainless steel  
Polyoxymethylene  
Die cast zinc; Brass, nickel-plated

#### Technical Remarks

- The series QR1 (plastic) and QR2 (metal) can not be combined
- For further information about assembling and tolerances of adaptable tubing, see the section "Technical information".

#### Dimensions



00117239

Part No.	Port D	Port G	Ø dx	A	B	F	X	Y	Delivery quantity [Piece]	Weight [lbs]
<b>2121204000</b>	Ø 4	Ø 4	2.2	18.7	16	6	12	10	10	0.0103
<b>2121206000</b>	Ø 6	Ø 6	3.2	20.4	17	8	14	12	10	0.0136
<b>2121208000</b>	Ø 8	Ø 8	4.2	22.8	18.5	10	16	14	10	0.0191
<b>2121210000</b>	Ø 10	Ø 10	4.2	26.1	21	12	19	17	10	0.0332
<b>2121212000</b>	Ø 12	Ø 12	4.2	29	22.5	14	23	21	10	0.0456
<b>2121214000</b>	Ø 14	Ø 14	-	32.1	24.6	13.5	25	23	5	0.0809
<b>R412005033</b>	Ø16	Ø16	5.3	31.1	24.8	16.3	27	24	5	0.0804

All dimensions in mm, unless specified otherwise.

Part numbers marked in bold are available from the central warehouse in Germany, see the shopping basket for more detailed information

Pneumatics catalog, online PDF, as of 2016-12-01, ©AVENTICS S.à r.l., subject to change