



RECTANGULAR POWER CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

M-SERIES KIT,V.35,34P,UNASSM

AMP | KT , KTT

213932-3

TE Internal Number: 213932-3

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Plug**

Connector System **Cable-to-Cable**

Applies To **Wire/Cable**

Number of Positions **34**

Product Drawings

CONNECTOR KIT, UNASSEMBLED, PLUG, 34 POSITION, M SERIES

PDF
English

CAD Files

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
English

Catalog Pages/Data Sheets

M_SERIES_PIN_AND_SOCKET_CONNECTORS

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type

Housing

Housing Type

Plug

Contact Type

Pin

Assembly or Kit

Kit

Configuration Features

Number of Positions

34

Configuration Details	Number of Positions	2
Mechanical Attachment	Panel Mount Retention	Without
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Black
	Housing Material	Polyester
Dimensions	Cable Diameter (Max)	13.83 mm [.544 in]
	Length	52.07 mm [2.05 in]
	Height	41.15 mm [1.62 in]
	Width	21.03 mm [.828 in]
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Cable-to-Cable
	Applies To	Wire/Cable
	Operating Temperature	-55 – 130 °C [-67 – 266 °F]
Industry Standards	Agency/Standard	CSA, UL
	Agency/Standard Number	E28476
Packaging Features	Packaging Method	Bag
	Packaging Quantity	1
Other	For Use With	Receptacle Connector Kit
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	