

Printed-circuit board connector - MSTBO 2,5/ 2-G1L YE - 2200357

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Header

The illustration shows the green product version



Key commercial data

Packing unit	1
GTIN	 4 046356 576758
Custom tariff number	85366990

Technical data

Product type	Printed circuit board housing
Approval	CSA
	UL Recognized
	VDE report with production monitoring
	cUL Recognized
	IECEE CB Scheme
	CCA
	cULus Recognized
Rated voltage (IEC)	320
Rated current (IEC)	12
Mounting type	Soldering
Number of positions	2
Pitch	5 mm
Levels	single-level
Type of locking	Without

Printed-circuit board connector - MSTBO 2,5/ 2-G1L YE - 2200357

Classifications

eCl@ss

eCl@ss 4.0	27260700
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260700
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

ETIM

ETIM 3.0	EC002637
ETIM 4.0	EC002637
ETIM 5.0	EC002637

UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	34131203
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

Approvals

Approvals

Approvals

CSA / UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / IECCE CB Scheme / CCA / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

CSA 		
	B	D
Nominal current I _N	10 A	10 A
Nominal voltage U _N	300 V	300 V

Printed-circuit board connector - MSTBO 2,5/ 2-G1L YE - 2200357

Approvals

UL Recognized 		
	B	D
Nominal current I _N	16 A	10 A
Nominal voltage U _N	300 V	300 V

VDE Gutachten mit Fertigungsüberwachung 	
Nominal current I _N	8 A
Nominal voltage U _N	250 V

cUL Recognized 		
	B	D
Nominal current I _N	16 A	10 A
Nominal voltage U _N	300 V	300 V

IECEE CB Scheme 	
Nominal current I _N	8 A
Nominal voltage U _N	250 V

CCA	
Nominal current I _N	8 A
Nominal voltage U _N	250 V

cULus Recognized 	
--	--