



BNC CONNECTORS



✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

RECEPTACLE,PRESS FIT,COML BNC FST

222006-1

TE Internal Number: 222006-1

Alias ID: 650-1095-01

[5 of 6 EU RoHS/ELV Compliant](#)

[Find Compliant Alternatives](#)

Applies To **Printed Circuit Board**

Panel Mount Retention **Without**

PCB Mount Retention **With**

PCB Termination Method **Through Hole**

Body Material **Zinc**

Product Drawings

[JACK, PCB, HIGH RETENTION PRESS FIT, 50 OHM, BNC](#)

PDF [\(TIFF AVAILABLE\)](#)
English

[JACK, PCB, HIGH RETENTION PRESS FIT, 50 OHM, BNC](#)

PDF [\(TIFF AVAILABLE\)](#)
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Product Specification

[Commercial Press-Fit BNC Coaxial PCB Receptacle Connector](#)

TIF
English

Application Specification

[Commercial Press-Fit BNC Coaxial PCB Receptacle Connector](#)

PDF
English

[Commercial 50- And 75-Ohm BNC Press-Fit Printed Circuit \(PC\) Board Coaxial RF Receptacle Connectors](#)

PDF
English

Qualification Test Report

[AMP Commercial Press Fit Printed Circuit Board Connectors](#)

PDF
English

[AMP Commercial Press Fit Printed Circuit Board Connectors](#)

TIF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Applies To	Printed Circuit Board
	Sealed	No
	RF Connector Type	BNC
	Connector Style	Jack
	PCB Mounting Orientation	Vertical
	Dielectric Material	PTFE
	ESD Protection	Without
	Isolated Ground	No
	Grade	Commercial
	Product Type	Connector - RF
Configuration Features	Solder Terminal	Without
	Number of Ports	1
Electrical Characteristics	50 Ohm	Yes
	75 Ohm	No
	Impedance (Ω)	50
Body Features	Body Material	Zinc
	Body Plating Material	Nickel
	Body Style	Straight
	Body Insulation	Without
	Body Shape	Circular
Contact Features	Center Contact Material	Beryllium Copper
	Center Contact Plating Material	Gold
	Center Contact Plating Thickness (μ in)	1080
Termination Features	PCB Termination Method	Through Hole
Mechanical Attachment	Panel Mount Retention	Without
	PCB Mount Retention	With
	Panel Mount	Without

	Polarized	No
	Hardware Included	No
Dimensions	Height above PCB	20.57 mm [.81 in]
Packaging Features	Packaging Method	Tube
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

OTHER AUTOMOTIVE
CONNECTOR ACCESSORIES

RECEPTACLE ASSEMBLY,
Shunt, MSD
1-1587987-7

Save to List

Find Similar Products

SURFACE MOUNT RESISTORS

RP 2A 6K19 0.1% 15PPM
CUT LENGTH
RP73D2A6K19BTG

Save to List

Find Similar Products

D-SUB CONNECTOR
CONTACTS

CONT, PIN, HDE, #18-22
1-745267-0

Save to List

Find Similar Products

MULTIPLE CONFIGURATION
PCB HEADERS & RECEPTACLES

04 MODII HDR SRRA SHRD
.100CL
102203-1

Save to List

Find Similar Products