


MALE PCB PINS

SOLDER TERMINALS PIN TYPE

2318

2318-X-00-XX-00-00-07-0

Swage mount in .062 hole




Basic Part Number	Board Thickness	Length V
2318-1	.031	.051
2318-2	.062	.082
2318-3	.094	.113

2309

2309-X-00-XX-00-00-07-0

Swage mount in .064 hole




Basic Part Number	Board Thickness	Length V
2309-1	.031	.054
2309-2	.062	.084
2309-3	.094	.115
2309-4	.125	.147

2514

2514-2-00-XX-00-00-07-0

Press-fit in .070 mounting hole



SPECIFICATIONS:

Pin Material: Brass Alloy 360, 1/2 Hard
(Swage pins are annealed)

Dimensions: Inches

Tolerances On: Lengths: ±.005
Diameters: ±.002
Angles: ± 2°



ORDER CODE: XXXX - X - 00 - XX - 00 - 00 - 07 - 0

BASIC PART #

SPECIFY PIN FINISH:

- 01 200 μ" TIN/LEAD OVER NICKEL
- ◆ 80 200 μ" TIN OVER NICKEL (RoHS)
- ◆ 44 300 μ" SILVER OVER COPPER (RoHS)
- 50 300 μ" ELECTRO-SOLDER
(60/40 SnPb)



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mill-Max:

[2514-2-00-01-00-00-07-0](#) [2514-2-00-50-00-00-07-0](#) [2318-3-00-50-00-00-07-0](#) [2318-2-00-01-00-00-07-0](#) [2318-2-00-50-00-00-07-0](#) [2318-1-00-01-00-00-07-0](#) [2318-1-00-50-00-00-07-0](#) [2309-4-00-01-00-00-07-0](#) [2309-4-00-50-00-00-07-0](#) [2309-3-00-01-00-00-07-0](#) [2309-3-00-50-00-00-07-0](#) [2309-2-00-01-00-00-07-0](#) [2309-2-00-50-00-00-07-0](#) [2309-1-00-01-00-00-07-0](#) [2309-1-00-50-00-00-07-0](#) [2318-3-00-01-00-00-07-0](#) [2309-1-00-44-00-00-07-0](#) [2309-2-00-44-00-00-07-0](#) [2309-3-00-44-00-00-07-0](#) [2309-4-00-44-00-00-07-0](#) [2318-1-00-44-00-00-07-0](#) [2318-2-00-44-00-00-07-0](#) [2318-3-00-44-00-00-07-0](#) [2514-2-00-44-00-00-07-0](#) [2309-1-00-00-00-00-07-0](#) [2309-2-00-00-00-00-07-0](#) [2309-3-00-00-00-00-07-0](#) [2318-1-00-00-00-00-07-0](#)