

Item no.: 232-306/026-000
 Product description: ANGLED FEMALE PLUG; 6 POLE; PIN SPACING 5.08 MM / 0.2 IN; WITH CODIG FINGERS; WITH INTEGRATED FIXING FLANGES; CONDUCTOR EXIT OPPOSITE TO LATCHES



Packing unit 25 pieces

Pin spacing from	5,08 mm
Pin spacing from	0,2 in
pole count	6
Cross section from [mm ²]	0,08 mm ²
Cross section to [mm ²]	2,5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP®CONNECTION
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	14 A
Voltage CSA	300 V
Current CSA	15 A
Voltage UL	300 V
Voltage UL	600 V
Current UL	15 A
Weight	11,256 g
Color	orange
No. of connection Points	6
No. of potentials	6
Height	23,9 mm



Width	32,88 mm
Width	1,294 in
Depth	22,75 mm
Depth	0,896 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0,33 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
232-306/026-000	BV	11915/A0	400	16	2,5
232-306/026-000	CSA	154112-1466354	300	15	22-12
232-306/026-000	DEMKO	88126	250		2,5
232-306/026-000	KEMA	98.2486.01	250	14	
232-306/026-000	KR	HMB05880-EL003	250/400	12/16	2,5
232-306/026-000	NEMKO	P94100799	250		2,5
232-306/026-000	UL	E45171	600	15	22-12
232-306/026-000	UL	E45172	300	15	22-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected