


Item no.: 243-144
 Product description: Micro push-wire connector for junction boxes 4-conductor terminal block



Produkt kann von Bild abweichen / product may differ

Packing unit 1000 10*100 pieces

RoHS compliant

Product group	7 (Push Wire Conn.)
pole count	4
Connection method	PUSH WIRE®
Cross section to [AWG]	24 AWG
Cross section [AWG]	26 - 0.4 mm
Diameter to	0.5 mm
Measured voltage EN	100 V
Measured shock voltage	1.5 kV
Pollution degree	2
Current intensity EN	6 A
Weight	0.81 g
Color	transparent
Wiring type	Side-entry
No. of connection Points	4
No. of potentials	1
Height	6.8 mm
Height	0.268 in
Width	10 mm
Width	0.394 in

Depth	10 mm
Depth	0.394 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
243-144	ABS	04-HG476172/1-PDA	100	6	0,5-0,75
243-144	LR	04/20013(E3)	100	6	0,5-0,75
243-144	RMR	11130002	100	6	0,5-0,75

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected