



SEMITOP® 3

IGBT Module

SK50GD066ET


Target Data

Features

- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)
- Trench IGBT technology
- CAL technology FWD
- Integrated NTC temperature sensor

Typical Applications*

- Inverter up to 12,5 kVA
- Typ. motor power 5,5 kW




GD-ET

Absolute Maximum Ratings		T _s = 25 °C, unless otherwise specified		
Symbol	Conditions	Values	Units	
IGBT				
V _{CES}	T _j = 25 °C	600	V	
I _C	T _j = 175 °C	T _s = 25 °C	60	A
		T _s = 70 °C	50	A
I _{CRM}	I _{CRM} = 2 x I _{Cnom}	100	A	
V _{GES}		± 20	V	
t _{psc}	V _{CC} = 360 V; V _{GE} ≤ 20 V; T _j = 150 °C V _{CES} < 600 V	6	μs	
Inverse Diode				
I _F	T _j = 175 °C	T _s = 25 °C	56	A
		T _s = 70 °C	44	A
I _{FRM}	I _{FRM} = 2 x I _{Fnom}	60	A	
I _{FSM}	t _p = 10 ms; half sine wave T _j = 150 °C	320	A	
Module				
I _{t(RMS)}			A	
T _{vj}		-40 ... +175	°C	
T _{stg}		-40 ... +125	°C	
V _{isol}	AC, 1 min.	2500	V	

Characteristics			T _s = 25 °C, unless otherwise specified			
Symbol	Conditions		min.	typ.	max.	Units
IGBT						
V _{GE(th)}	V _{GE} = V _{CE} , I _C = 0,8 mA		5	5,8	6,5	V
I _{CES}	V _{GE} = 0 V, V _{CE} = V _{CES}	T _J = 25 °C T _J = 150 °C				mA mA
I _{GES}	V _{CE} = 0 V, V _{GE} = 20 V	T _J = 25 °C T _J = 150 °C	600			nA nA
V _{CE0}		T _J = 25 °C T _J = 150 °C		0,9 0,8	1,1 1	V V
r _{CE}	V _{GE} = 15 V	T _J = 25°C T _J = 150°C		11 17	15 21	mΩ mΩ
V _{CE(sat)}	I _{Cnom} = 50 A, V _{GE} = 15 V	T _J = 25°C _{chiplev.} T _J = 150°C _{chiplev.}		1,45 1,65	1,85 2,05	V V
C _{ies} C _{oes} C _{res}	V _{CE} = 25, V _{GE} = 0 V	f = 1 MHz		3,1 0,2 0,093		nF nF nF
Q _G	V _{GE} = -7V...+15V			250		nC
t _{d(on)} t _r E _{on}	R _{Gon} = 16 Ω di/dt = 2438 A/μs	V _{CC} = 300V I _C = 50A		28 32 2,2		ns ns mJ
t _{d(off)} t _f E _{off}	R _{Goff} = 16 Ω di/dt = 2438 A/μs	T _J = 150 °C V _{GE} = -7/+15V		301 45 1,73		ns ns mJ
R _{th(j-s)}	per IGBT			1,11		K/W

SK50GD066ET



IGBT Module

SK50GD066ET


Target Data

Features

- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)
- Trench IGBT technology
- CAL technology FWD
- Integrated NTC temperature sensor

Typical Applications*






- Inverter up to 12,5 kVA
- Typ. motor power 5,5 kW







Characteristics					
Symbol	Conditions	min.	typ.	max.	Units
Inverse Diode					
$V_F = V_{EC}$	$I_{Fnom} = 50\text{ A}; V_{GE} = 0\text{ V}$		$T_j = 25\text{ °C}_{chiplev.}$ $T_j = 150\text{ °C}_{chiplev.}$	1,5 1,5	V V
V_{F0}			$T_j = 25\text{ °C}$ $T_j = 150\text{ °C}$	1 0,9	1,1 1 V V
r_F			$T_j = 25\text{ °C}$ $T_j = 150\text{ °C}$	10 12	12 14 mΩ mΩ
I_{RRM}	$I_F = 50\text{ A}$		$T_j = 150\text{ °C}$	44	A
Q_{rr}	$di/dt = 2438\text{ A/μs}$			4,8	μC
E_{rr}	$V_{CC} = 300\text{ V}$			0,72	mJ
$R_{th(j-s)D}$	per diode			1,7	K/W
M_s	to heat sink	2,25		2,5	Nm
w			30		g
Temperature sensor					
R_{100}	$T_s = 100\text{ °C}$ ($R_{25} = 5\text{ kΩ}$)			493±5%	Ω

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.


* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.







Case T52 (Suggested hole diameter, in the PCB, for solder pins and plastic mounting pins: 2mm)



Case T 52

GD-ET