


USB 2.0 Compliant Bulk Cable, Black Specifications

STYLE	USB2.0 UL2725 28#/1P+24#/2C+AEB		DOCUMENT NO.	VG0942016042902	
CONSTRUCTION ITEM 结构项目			1P		2C
CONDUCTOR 导体	SIZE 规格		28AWG		24AWG
	MATERIAL 材质		TC		TC
	CONSTRUCTION 结构		7/0.12±0.008mm		7/0.20±0.008mm
INSULATION 绝缘	AVG. THICK 平均厚度		0.22mm		0.24mm
	MIN. THICK 最小厚度		0.15mm		0.17mm
	MATERIAL 材质		HDPE		SR-PVC
	DIAMETER 完成外径		0.85±0.05mm		1.00±0.05mm
SHIELDED 隔离	FILLET SHIELD 填充材质		-----		
	AL/MYLAR MATERIAL 铝箔材质		AL/MYLAR		
	AL/MYLAR CONSTRUCTION 铝箔结构		12/0.02mm		
	MYLAR MATERIAL 麦拉材质		-----		
	MYLAR CONSTRUCTION 麦拉结构		-----		
	DRAIN MATERIAL 地线材质		TC		
	DRAIN CONSTRUCTION 地线结构		7/0.12±0.008mm		
	BRAID MATERIAL 编织材质		TC		
	BRAID CONSTRUCTION 编织结构		16/4/0.12±0.008mm		7—8目
COVERED 中被	AVG. THICK 平均厚度		-----		
	MIN. THICK 最小厚度		-----		
	MATERIAL 材质		-----		
	DIAMETER 完成外径		-----		
	COLOR 颜色		-----		
JACKET 外被	AVG. THICK 平均厚度		0.93mm		
	MIN. THICK 最小厚度		0.79mm		
	MATERIAL 材质		65P UL-PVC ALL raw materials meet rohs standards		
	DIAMETER 完成外径		4.5±0.15mm		
	COLOR 颜色		IV-29# (HALF ATOMIZER)		
MARKING 印字	MARKING NO. 内容(513#)	USB HIGH SPEED CABLE 2.0 REVISION E189529  AWM 2725 28AWG/1PR AND 24AWG/2C 80℃ 30V VW-1			
	COLOR 颜色	BLACK			
CONSTRUCTION DRAWING & COLOR 线材结构图及颜色					
			芯线颜色: 1P: WHITE, GREEN 2C: RED, BLACK		
ELECTRICAL CHARACTERISTICS 电气特性					
1. Conductor Resistance: AT 20℃ Max: A: 237.25 OHM/KM B: 93.25 OHM/KM					
2. Insulation Resistance: AT 20℃ Min: 10M Ω/KM					
3. Dielectric Strength: AC500V 60HZ/分钟					