

UFBK 2/2- 5DC-HF-BE

This product has been replaced by a newer version.

Order No.: 2781301

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2781301>

Base element for protective plug UFBK 2/2 -5 V DC-HF-ST, with universal foot for mounting on DIN rail NS 35 or NS 35/7,5, nominal voltage: 5 V DC

Commercial data

EAN	4017918068936
Pack	10 pcs.
Customs tariff	85363010
Weight/Piece	0.05552 KG

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Product description

Base element to accept a protective plug: UFBK 2/2-5 DC-HF-ST.

Technical data

General

Stripping length	8 mm
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Nominal current I _N	200 mA
Ambient temperature (operation)	-20 °C ... 60 °C
Housing material	PA
Inflammability class acc. to UL 94	V2

Degree of protection	IP20
Pitch unit	1 Div.

Certificates / Approvals

UL

Nominal voltage U_N	5 V
Nominal current I_N	0.1 A
AWG/kcmil	22-12

Accessories

Item	Designation	Description
------	-------------	-------------

Marking

2715212	ZB 5,8,LGS:FORTL.ZAHLEN	Zack marker strip, 10-section, printed horizontally: with consecutive numbers, 1-10, 11-20 etc. up to 991-1000, color: white
1050305	ZB 5,8:SO/CMS	Zack strip, 10-section, divisible, special printing, marking according to customer requirements
2715209	ZB 5,8:UNBEDRUCKT	Zack strip, unprinted, strips with 10 labels for individual labeling with M-PEN or CMS system, for terminal block width: 5.8 mm, color: White

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2009 Phoenix Contact
Technical modifications reserved;