

Surge protection device - DT-TELE-RJ45 - 2882925

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Attachment plug with surge protection for analog and digital telecommunications interfaces (VDSL up to 50 Mbps). Connection: RJ45 (RJ12/RJ11) and screw terminal block (COMBICON). Alternatively, can be snapped onto a DIN rail.

Why buy this product

- ✓ For analog and digital (DSL) telecommunications interface
- ✓ Connection: RJ45 socket and/or plug-in screw terminal blocks
- ✓ The adapter included enables conversion from RJ45 to RJ11 and RJ12
- ✓ DIN rail mounting possible by removing the cover cap
- ✓ International use thanks to multiple assignment



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 155137
GTIN	4046356155137
Weight per Piece (excluding packing)	332.600 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Height	102 mm
Width	25 mm
Depth	63.5 mm

Ambient conditions

Surge protection device - DT-TELE-RJ45 - 2882925

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Degree of protection	IP20

General

Housing material	Zinc die-cast
Color	silver/black
Mounting type	Connection-specific attachment plug and DIN rail, 35 mm
Type	Attachment plug for DIN rail mounting
Number of positions	4
Direction of action	Line-Line & Line-Ground/Shield

Protective circuit

IEC test classification	B2
	C1
	C2
	C3
	D1
Maximum continuous voltage U_C	185 V DC
	130 V AC
Rated current	≤ 380 mA (25 °C)
Operating effective current I_C at U_C	≤ 6 μ A
Residual current I_{PE}	≤ 4 μ A
Nominal discharge current I_n (8/20) μ s (Core-Core)	≤ 5 kA
Nominal discharge current I_n (8/20) μ s (core-earth)	≤ 5 kA
Total discharge current I_{total} (8/20) μ s	10 kA
Nominal pulse current I_{an} (10/1000) μ s (Core-Core)	100 A
Nominal pulse current I_{an} (10/1000) μ s (Core-Earth)	100 A
Nominal pulse current I_{an} (10/700) μ s (Core-Core)	150 A
Nominal pulse current I_{an} (10/700) μ s (Core-Earth)	150 A
Output voltage limitation at 1 kV/ μ s (core-core) static	≤ 250 V
Output voltage limitation at 1 kV/ μ s (core-earth) static	≤ 250 V
Residual voltage at I_n (conductor-conductor)	≤ 120 V
Residual voltage at I_n (conductor-ground)	≤ 120 V
Voltage protection level U_p (core-core)	≤ 250 V (B2 - 4 kV / 100 A)
	≤ 250 V (C1 - 1 kV/500 A)
	≤ 250 V (C2 - 10 kV / 5 kA)
Voltage protection level U_p (core-ground)	≤ 250 V (B2 - 4 kV / 100 A)

Surge protection device - DT-TELE-RJ45 - 2882925

Technical data

Protective circuit

	$\leq 250 \text{ V}$ (C1 - 1 kV/500 A)
	$\leq 250 \text{ V}$ (C2 - 10 kV / 5 kA)
Response time t_A (core-core)	$\leq 100 \text{ ns}$
Response time t_A (core-earth)	$\leq 100 \text{ ns}$
Input attenuation a_E , sym.	typ. 0.5 dB ($\leq 5 \text{ MHz}$ / 100Ω)
	typ. 0.3 dB ($\leq 8 \text{ MHz}$ / 150Ω)
	typ. 0.3 dB ($\leq 2.5 \text{ MHz}$ / 600Ω)
Cut-off frequency f_g (3 dB), sym. in 100Ω system	typ. 50 MHz
Capacity (core-core)	typ. 20 pF ($f = 1 \text{ MHz}$ / $V_R = 0 \text{ V}$)
Capacity (core-earth)	typ. 20 pF ($f = 1 \text{ MHz}$ / $V_R = 0 \text{ V}$)
Resistance in series	3.3Ω 10 %
Surge protection fault message	none
Impulse durability (conductor-conductor)	B2 - 4 kV/100 A
	C1 - 1 kV/500 A
	C2 - 10 kV/5 kA
Impulse durability (conductor-ground)	B2 - 4 kV/100 A
	C1 - 1 kV/500 A
	C2 - 10 kV/5 kA
	D1 - 1 kA

Connection data

Connection method	RJ45/COMBICON
Connection method IN	RJ45 socket
	MC 1,5/4
Connection method OUT	RJ45 socket
	MC 1,5/4
Connection technology	Screw connection
Screw thread	M2
Tightening torque	0.22 Nm
Stripping length	7 mm
Conductor cross section flexible	$0.14 \text{ mm}^2 \dots 1.5 \text{ mm}^2$
Conductor cross section solid	$0.14 \text{ mm}^2 \dots 1.5 \text{ mm}^2$
Conductor cross section AWG	28 ... 16

Connection, equipotential bonding

Connection method	DIN rail NS35
-------------------	---------------

Standards and Regulations

Standards/specifications	IEC 61643-21 2012
--------------------------	-------------------

Surge protection device - DT-TELE-RJ45 - 2882925

Technical data

Standards and Regulations


	EN 61643-21 2013
--	------------------

Environmental Product Compliance


China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Circuit diagram



Dimensional drawing



Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 7.0	27130807
eCl@ss 8.0	27130807
eCl@ss 9.0	27130807

ETIM

ETIM 2.0	EC000943
ETIM 3.0	EC000943
ETIM 4.0	EC000943
ETIM 5.0	EC000943
ETIM 6.0	EC000943

Surge protection device - DT-TELE-RJ45 - 2882925

Classifications

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Approval details

EAC		RU C- DE.A*30.B01561
-----	---	-------------------------

EAC		EAC-Zulassung
-----	---	---------------