

WITHOUT PRIOR WRITTEN
FROM KEYSTONE ELECTRONICS

REEL DIA. REF.

FEED DIRECTION

.500 [12.7] DIA. HOLE THRU

$\pm .030 [\pm 0.78]$

.100 [2.54]

3.937 [100.0] REF.

$\pm .005 [\pm 0.15]$

.157 [4.0]

$\pm .005 [\pm 0.15]$

.059 [1.5] DIA. HOLE (TYP.)

$\pm .005 [\pm 0.15]$ PITCH

.071 [1.80]

.130 [3.30]

$\pm .005 [\pm 0.15]$ WIDTH

FEED DIRECTION

.467 [11.85]

.016 [0.4] REF.

TAPE AND REEL SPECIFICATIONS:

- | | | |
|---------|---------------------------|------|
| 4.09.12 | CHANGE AS PER ECN 12-044 | B |
| 3.07.11 | CHAQNGE AS PER ECN 11-028 | A |
| DATE | DESCRIPTION | REV. |

KEYSTONE ELECTRONICS CORP. www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900			
PART NAME BATTERY CONTACT, ON TAPE			
MATERIAL AS NOTED			
FINISH AS NOTED		DRN BY NT	DATE 10.09.09
		APP'D LN	SCALE X
TOLERANCES DECIMAL $\pm .015$ [MM] $[\pm 0.38]$ ANGULAR $\pm 1^\circ$ UNLESS OTHERWISE SPECIFIED	INCH C/M	DWG NO. 2993TR	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Keystone Electronics:](#)

[2993TR](#)