

TABLE B

UNIUNCTION TRANSISTORS

TO-18 CASE

CENTRAL SEMICONDUCTOR

61 DE 1989963 0000237 9

T-37-21

TYPE	INTRINSIC STANDOFF RATIO η		INTERBASE RESISTANCE r_{BB}		PEAK-POINT CURRENT I_p	EMITTER REV. CURRENT $I_{EB20} @ V_{B2E}$		VALLEY-POINT CURRENT I_V	BASE 1 PEAK VOLTAGE V_{OB1}	CASE
	MIN.	MAX.	MIN.	MAX.	MAX.	MAX.		MIN.	MIN.	
			k Ω	k Ω	μA	μA	V	mA	V	
2N2417	0.51	0.62	4.7	6.8	12	2.0	60	8.0	—	
2N2417A	0.51	0.62	4.7	6.8	12	2.0	60	8.0	3.0	
2N2417B	0.51	0.62	4.7	6.8	6.0	0.2	30	8.0	3.0	
2N2418	0.51	0.62	6.2	9.1	12	2.0	60	8.0	—	
2N2418A	0.51	0.62	6.2	9.1	12	2.0	60	8.0	3.0	
2N2418B	0.51	0.62	6.2	9.1	6.0	0.2	30	8.0	3.0	
2N2419	0.56	0.68	4.7	6.8	12	2.0	60	8.0	—	
2N2419A	0.56	0.68	4.7	6.8	12	2.0	60	8.0	3.0	
2N2419B	0.56	0.68	4.7	6.8	6.0	0.2	30	8.0	3.0	
2N2420	0.56	0.68	6.2	9.1	12	2.0	60	8.0	—	
2N2420A	0.56	0.68	6.2	9.1	12	2.0	60	8.0	3.0	
2N2420B	0.56	0.68	6.2	9.1	6.0	0.2	30	8.0	3.0	
2N2421	0.62	0.75	4.7	6.8	12	2.0	60	8.0	—	
2N2421A	0.62	0.75	4.7	6.8	12	2.0	60	8.0	3.0	
2N2421B	0.62	0.75	4.7	6.8	6.0	0.2	30	8.0	3.0	
2N2422	0.62	0.75	6.2	9.1	12	2.0	60	8.0	—	
2N2422A	0.62	0.75	6.2	9.1	12	2.0	60	8.0	3.0	
2N2422B	0.62	0.75	6.2	9.1	6.0	0.2	30	8.0	3.0	
2N2646	0.56	0.75	4.7	9.1	5.0	12	30	4.0	3.0	
2N2647	0.68	0.82	4.7	9.1	2.0	0.2	30	8.0	6.0	
2N2840	0.62*	—	4.7	9.1	10	1.0	30	.20	—	
2N3980	0.68	0.82	4.0	8.0	2.0	0.01	30	1.0	6.0	
2N4851	0.56	0.75	4.7	9.1	2.0	0.1	30	2.0	3.0	
2N4852	0.70	0.85	4.7	9.1	2.0	0.1	30	4.0	5.0	
2N4853	0.70	0.85	4.7	9.1	0.4	0.05	30	6.0	6.0	
2N4947	0.51	0.69	4.0	9.1	2.0	0.01	30	4.0	3.0	
2N4948	0.55	0.82	4.0	12	2.0	0.01	30	2.0	6.0	
2N4949	0.74	0.86	4.0	12	1.0	0.01	30	2.0	3.0	
2N5431	0.72	0.80	6.0	8.5	0.4	0.01	30	2.0	1.0	
MU20	0.50	0.85	4.0	10	5.0	1.0	30	1.0	3.0	
MU2646M	0.56	0.75	4.7	9.1	5.0	12	30	2.0	3.0	

*Typical Value

TABLE C

UNIUNCTION TRANSISTORS

TO-92 CASE


TYPE	INTRINSIC STANDOFF RATIO η		INTERBASE RESISTANCE r_{BB}		PEAK-POINT CURRENT I_p	EMITTER REV. CURRENT $I_{EB20} @ V_{B2E}$		VALLEY-POINT CURRENT I_V	BASE 1 PEAK VOLTAGE V_{OB1}	CASE
	MIN.	MAX.	MIN.	MAX.	MAX.	MAX.		MIN.	MIN.	
			k Ω	k Ω	μA	μA	V	mA	V	
2N4870	0.56	0.75	4.0	9.1	5.0	1.0	30	2.0	3.0	
2N4871	0.70	0.85	4.0	9.1	5.0	1.0	30	4.0	5.0	
MU10	0.50	0.85	4.0	10	5.0	1.0	30	1.0	3.0	
MU2646	0.56	0.75	4.7	9.1	5.0	12	30	4.0	3.0	
MU4891	0.55	0.82	4.0	9.1	5.0	0.01	30	2.0	3.0	
MU4892	0.51	0.69	4.0	9.1	2.0	0.01	30	2.0	3.0	
MU4893	0.55	0.82	4.0	12	2.0	0.01	30	2.0	6.0	
MU4894	0.74	0.86	4.0	12	1.0	0.01	30	2.0	3.0	


TABLE D

PROGRAMMABLE UNIUNCTION TRANSISTORS


TO-92 CASE

TYPE	MAXIMUM RATINGS		GATE TO ANODE LEAKAGE CURRENT $I_{GAO} @ 40v$	PEAK CURRENT I_P		VALLEY CURRENT I_V	
	GATE TO ANODE REVERSE VOLTAGE V_{GAR}	DC ANODE CURRENT I_T		$R_G = 10k\Omega$	$R_G = 1.0M\Omega$	$R_G = 10k\Omega$	$R_G = 1.0M\Omega$
	MAX.	MAX.	MAX.	MIN.	MAX.		
V	mA	nA	μA	μA	μA	μA	
2N6027	40	150	10	5.0	2.0	70	50
2N6028	40	150	10	1.0	0.15	25	25
A7T6027	40	150	10	5.0	2.0	70	50
A7T6028	40	150	10	1.0	0.15	25	25


CASE OUTLINE DRAWINGS

**LEAD CODE:**


1. BASE 1
2. EMITTER
3. BASE 2

TO-92 (UJT)**LEAD CODE:**

1. ANODE (A)
2. GATE (G)
3. CATHODE (K)

TO-92 (PUT)**LEAD CODE:**

1. EMITTER
2. BASE 1
4. BASE 2

TO-18***LEAD CODE:**

1. EMITTER
2. BASE 1
4. BASE 2

TO-5*

DIMENSIONS IN INCHES (MILLIMETERS)

DRAWINGS NOT TO SCALE.

*Conforms to JEDEC outline except for lead configuration.

TM


Central Semiconductor Corp.

145 Adams Avenue
Hauppauge, NY 11788
Tel: (516) 435-1110
TWX: (510) 224-6493


MANUFACTURERS OF DISCRETE SEMICONDUCTORS

CASE OUTLINE DRAWINGS


D



CASE A


CBR1 Series
CBR2 Series

CASE B

CBR1-L Series
CBR2-L Series


CASE C

CBR3-P Series




CASE D

CBR4-L Series



CASE E

CBR8 Series



CASE F


CBR10 Series, CBR25 Series
CBR12 Series, CBR30 Series

All Dimensions in Inches (Millimeters)


Drawings Not To Scale

カ

TO-39



TO-92



TO-106

