

Distributed by:



www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

Amplifier Transistors

NPN Silicon

2N5088
2N5089

MAXIMUM RATINGS

Rating	Symbol	2N5088	2N5089	Unit
Collector-Emitter Voltage	V_{CEO}	30	25	Vdc
Collector-Base Voltage	V_{CBO}	35	30	Vdc
Emitter-Base Voltage	V_{EBO}	3.0		Vdc
Collector Current — Continuous	I_C	50		mAdc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above 25°C	P_D	625	5.0	mW mW/ $^\circ\text{C}$
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	1.5	12	Watts mW/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-55 to +150		$^\circ\text{C}$

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Ambient	$R_{\theta JA}^{(1)}$	200	$^\circ\text{C/W}$
Thermal Resistance, Junction to Case	$R_{\theta JC}$	83.3	$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)


Characteristic	Symbol	Min	Max	Unit

OFF CHARACTERISTICS


Collector-Emitter Breakdown Voltage ⁽²⁾ ($I_C = 1.0$ mA, $I_B = 0$) 2N5088 2N5089	$V_{(BR)CEO}$	30 25	—	Vdc
Collector-Base Breakdown Voltage ($I_C = 100$ μ Adc, $I_E = 0$) 2N5088 2N5089	$V_{(BR)CBO}$	35 30	—	Vdc
Collector Cutoff Current ($V_{CB} = 20$ Vdc, $I_E = 0$) ($V_{CB} = 15$ Vdc, $I_E = 0$) 2N5088 2N5089	I_{CBO}	— —	50 50	nAdc
Emitter Cutoff Current ($V_{EB(off)} = 3.0$ Vdc, $I_C = 0$) ($V_{EB(off)} = 4.5$ Vdc, $I_C = 0$)	I_{EBO}	— —	50 100	nAdc

1. $R_{\theta JA}$ is measured with the device soldered into a typical printed circuit board.

2. Pulse Test: Pulse Width ≤ 300 μ s, Duty Cycle $\leq 2.0\%$.



CASE 29-11, STYLE 1
TO-92 (TO-226AA)



2N5088 2N5089

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted) (Continued)

Characteristic	Symbol	Min	Max	Unit
ON CHARACTERISTICS				
DC Current Gain ($I_C = 100 \mu\text{A}_{\text{dc}}$, $V_{CE} = 5.0 \text{ V}_{\text{dc}}$)	h_{FE} 2N5088 2N5089	300 400	900 1200	—
($I_C = 1.0 \text{ mA}_{\text{dc}}$, $V_{CE} = 5.0 \text{ V}_{\text{dc}}$)	h_{FE} 2N5088 2N5089	350 450	—	—
($I_C = 10 \text{ mA}_{\text{dc}}$, $V_{CE} = 5.0 \text{ V}_{\text{dc}}$) ⁽²⁾	h_{FE} 2N5088 2N5089	300 400	—	—
Collector-Emitter Saturation Voltage ($I_C = 10 \text{ mA}_{\text{dc}}$, $I_B = 1.0 \text{ mA}_{\text{dc}}$)	$V_{CE(\text{sat})}$	—	0.5	V_{dc}
Base-Emitter On Voltage ($I_C = 10 \text{ mA}_{\text{dc}}$, $V_{CE} = 5.0 \text{ V}_{\text{dc}}$) ⁽²⁾	$V_{BE(\text{on})}$	—	0.8	V_{dc}

SMALL-SIGNAL CHARACTERISTICS

Current-Gain — Bandwidth Product ($I_C = 500 \mu\text{A}_{\text{dc}}$, $V_{CE} = 5.0 \text{ V}_{\text{dc}}$, $f = 20 \text{ MHz}$)	f_T	50	—	MHz
Collector-Base Capacitance ($V_{CB} = 5.0 \text{ V}_{\text{dc}}$, $I_E = 0$, $f = 1.0 \text{ MHz}$)	C_{cb}	—	4.0	pF
Emitter-Base Capacitance ($V_{EB} = 0.5 \text{ V}_{\text{dc}}$, $I_C = 0$, $f = 1.0 \text{ MHz}$)	C_{eb}	—	10	pF
Small-Signal Current Gain ($I_C = 1.0 \text{ mA}_{\text{dc}}$, $V_{CE} = 5.0 \text{ V}_{\text{dc}}$, $f = 1.0 \text{ kHz}$)	h_{fe} 2N5088 2N5089	350 450	1400 1800	—
Noise Figure ($I_C = 100 \mu\text{A}_{\text{dc}}$, $V_{CE} = 5.0 \text{ V}_{\text{dc}}$, $R_S = 1.0 \text{ k}\Omega$, $f = 1.0 \text{ kHz}$)	NF 2N5088 2N5089	— —	3.0 2.0	dB

2. Pulse Test: Pulse Width $\leq 300 \mu\text{s}$, Duty Cycle $\leq 2.0\%$.




Figure 1. Transistor Noise Model

NOISE CHARACTERISTICS

(V_{CE} = 5.0 Vdc, T_A = 25°C)

NOISE VOLTAGE




Figure 2. Effects of Frequency




Figure 3. Effects of Collector Current




Figure 4. Noise Current




Figure 5. Wideband Noise Figure

100 Hz NOISE DATA




Figure 6. Total Noise Voltage




Figure 7. Noise Figure

2N5088 2N5089




Figure 8. DC Current Gain




Figure 9. "On" Voltages




Figure 10. Temperature Coefficients




Figure 11. Capacitance






Figure 12. Current-Gain — Bandwidth Product

PACKAGE DIMENSIONS

TO-92 (TO-226)
CASE 29-11
ISSUE AL

SECTION X-X

STYLE 1:
 PIN 1. Emitter
 2. Base
 3. Collector

NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---

Notes

Notes

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

Literature Fulfillment:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

JAPAN: ON Semiconductor, Japan Customer Focus Center
4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031
Phone: 81-3-5740-2700
Email: r14525@onsemi.com

ON Semiconductor Website: <http://onsemi.com>
For additional information, please contact your local
Sales Representative.