

Normally – OFF Silicon Carbide Super Junction Transistor


V_{DS}	=	650 V
V_{DS(ON)}	=	1.5 V
I_D	=	15 A
R_{DS(ON)}	=	105 mΩ

Features

- 250 °C maximum operating temperature
- Temperature independent switching performance
- Electrically isolated base-plate
- Gate oxide free SiC switch
- Suitable for connecting an anti-parallel diode
- Positive temperature coefficient for easy paralleling
- Low gate charge
- Low intrinsic capacitance

Package

- RoHS Compliant



TO – 257 (Isolated Base-plate Hermetic Package)

Advantages

- Low switching losses
- Higher efficiency
- High temperature operation
- High short circuit withstand capability

Applications

- Down Hole Oil Drilling, Geothermal Instrumentation
- Hybrid Electric Vehicles (HEV)
- Solar Inverters
- Switched-Mode Power Supply (SMPS)
- Power Factor Correction (PFC)
- Induction Heating
- Uninterruptible Power Supply (UPS)
- Motor Drives

Maximum Ratings at T_j = 250 °C, unless otherwise specified

Parameter	Symbol	Conditions	Values	Unit
Drain – Source Voltage	V _{DS}	V _{GS} = 0 V	650	V
Continuous Drain Current	I _D	T _C = 155 °C	15	A
Gate Peak Current	I _{GM}		5	A
Reverse Gate – Source Voltage	V _{GS}		200	V
Reverse Drain – Source Voltage	V _{DS}		40	V
Power Dissipation	P _{tot}	T _C = 25 °C	22	W
Operating and Storage Temperature	T _j , T _{stg}		-55 to 250	°C

Electrical Characteristics at T_j = 250 °C, unless otherwise specified

Parameter	Symbol	Conditions	Values		
			min.	typ.	max.

On Characteristics

Drain – Source On Voltage	V _{DS(ON)}	I _D = 15 A, I _G = 500 mA, T _j = 25 °C I _D = 15 A, I _G = 1000 mA, T _j = 175 °C I _D = 15 A, I _G = 1000 mA, T _j = 250 °C	1.5 2.4 3.6		V
Drain – Source On Resistance	R _{DS(ON)}	I _D = 15 A, I _G = 500 mA, T _j = 25 °C I _D = 15 A, I _G = 1000 mA, T _j = 175 °C I _D = 15 A, I _G = 1000 mA, T _j = 250 °C	105 180 290		mΩ
Gate Forward Voltage	V _{GS(FWD)}	I _G = 500 mA, T _j = 25 °C I _G = 500 mA, T _j = 250 °C	3 2.6		V
DC Current Gain	β	V _{DS} = 5 V, I _D = 20 A, T _j = 25 °C V _{DS} = 5 V, I _D = 20 A, T _j = 250 °C	115 75		

Off Characteristics



Drain Leakage Current	I _{DS}	V _R = 650 V, V _{GS} = 0 V, T _j = 25 °C V _R = 650 V, V _{GS} = 0 V, T _j = 175 °C V _R = 650 V, V _{GS} = 0 V, T _j = 250 °C	1 7 45		μA
-----------------------	-----------------	---	--------------	--	----

Electrical Characteristics at $T_J = 250^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values		
			min.	typ.	max.
Dynamic Characteristics					
Input Capacitance	C_{iss}	$V_{DS} = 35\text{ V}, V_{GS} = 0\text{ V},$ $f = 1\text{ MHz}, T_J = 25^\circ\text{C}$	1534		pF
Output Capacitance	C_{oss}		157		pF
Reverse Transfer Capacitance	C_{rss}		157		pF
Switching Characteristics					
Turn On Delay Time	$t_{d(on)}$	$V_{DD} = 400\text{ V}, I_D = 20\text{ A},$ $R_{G(on)} = R_{G(off)} = 22\text{ }\Omega,$ $V_{GS} = -8/15\text{ V}, T_J = 175^\circ\text{C}$ Refer to Figure 10 for gate drive current waveforms	5		ns
Rise Time	t_r		37		ns
Turn Off Delay Time	$t_{d(off)}$		68		ns
Fall Time	t_f		78		ns
Turn-On Energy Per Pulse	E_{on}		66		μJ
Turn-Off Energy Per Pulse	E_{off}		365		μJ
Total Switching Energy	E_{ts}		431		μJ
Turn On Delay Time	$t_{d(on)}$		7		ns
Rise Time	t_r	$V_{DD} = 400\text{ V}, I_D = 10\text{ A},$ $R_{G(on)} = R_{G(off)} = 22\text{ }\Omega,$ $V_{GS} = -8/15\text{ V}, T_J = 250^\circ\text{C}$ Refer to Figure 10 for gate drive current waveforms	38		ns
Turn Off Delay Time	$t_{d(off)}$		85		ns
Fall Time	t_f		86		ns
Turn-On Energy Per Pulse	E_{on}		64		μJ
Turn-Off Energy Per Pulse	E_{off}		395		μJ
Total Switching Energy	E_{ts}		459		μJ

Thermal Characteristics

Thermal resistance, junction - case	R_{thJC}	1.4	$^\circ\text{C/W}$
-------------------------------------	------------	-----	--------------------


Figure 1: Typical Output Characteristics at 25°C

Figure 2: Typical Output Characteristics at 175°C




Figure 3: Typical Output Characteristics at 250 °C




Figure 4: Typical Gate Source I-V Characteristics vs. Temperature




Figure 5: Normalized On-Resistance and Current Gain vs. Temperature




Figure 6: Typical Blocking Characteristics




Figure 7: Typical Capacitance vs Drain-Source Voltage




Figure 8: Typical Turn On Energy Losses and Switching Times vs. Temperature




Figure 9: Typical Turn Off Energy Losses and Switching Times vs. Temperature





Figure 10: Typical Gate-Source Switching Waveforms

Package Dimensions:



NOTE

1. CONTROLLED DIMENSION IS INCH. DIMENSION IN BRACKET IS MILLIMETER.
2. DIMENSIONS DO NOT INCLUDE END FLASH, MOLD FLASH, MATERIAL PROTRUSIONS

Revision History			
Date	Revision	Comments	Supersedes
2012/08/24	0	Initial release	

Published by

GeneSiC Semiconductor, Inc.
43670 Trade Center Place Suite 155
Dulles, VA 20166

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice.

GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.