



3-1563759-1 Product Details

[Share](#) [Print](#) [Email](#)



3-1563759-1

TE Internal Number: 3-1563759-1
✔ Active

[View 3D PDF](#)

Multiple Contact Point (MCP) & MCON Contact Systems

✔ Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- HDSCS Product Line, Multiple Contact Point (MCP) Product Line
- Wire-to-Wire
- Applies To Wire/Cable
- Connector
- Housing

[View all Features](#)

Quick Links

- ▶ Pricing & Availability
- ▶ Search for Tooling
- ▶ Product Feature Selector
- ▶ Contact Us About This Product

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [18POS. AMP MCP 1.5k REC. HSG. ASSY 18pos. AMP MCP 1.... \(TIF, English\)](#)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [Heavy Duty Sealed Connector Series 2 to 18 positions... \(PDF, German\)](#)

Application Specifications:

- [Heavy Duty Sealed Connector Series \(HDSCS\) 2 to 18 p... \(PDF, English\)](#)

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- [2D Drawing \(DXF, Version J\)](#)
- [3D Model \(IGES, Version J\)](#)
- [3D Model \(STEP, Version J\)](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Line = HDSCS, Multiple Contact Point (MCP)
- Product Type = Connector
- Connector Type = Housing
- [Wire/Cable Type](#) = FLR (Thin Walled Cable)
- PCB Mount Retention = Without
- Key Type = Standard
- Sealed = Yes

Mechanical Attachment:

- Contact Retention = With
- Contact Retention Type = Secondary Locking/Retainer
- Mating Retention Type = Latching
- Panel Mount Retention = Without

Electrical Characteristics:

- Operating Voltage (VDC) = 42
- Operating Voltage Reference = DC

Termination Features:

- Termination Method to Wire/Cable = Crimp
- Seal Type = Radial Seal

Dimensions:

- Mating Area Interface Dimensions (mm [in]) = 1.50 [.059]

Body Features:

- Cable Exit Angle = 180°
- Assembly Integration Feature = With

Housing Features:

- Connector Style = Receptacle
- Housing Material = PBT - GF30
- Housing Color = Black
- Mating Alignment = With
- Mating Alignment Type = Keyed

Configuration Features:

- Number of Positions = 18
- Number of Rows = 2
- Strain Relief = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- UL Flammability Rating = UL 94V-0

Identification Marking:

- Keying = C

Environmental:

- Operating Temperature (°C [°F]) = -40 - +140 [-40 - +284]

Conditions for Usage:

- Applies To = Wire/Cable

Operation/Application:

- Application Use = Wire-to-Wire

Feedback

- Assembly Integration Type = Slide
- Mating Retention = With
- Wire Type = Stranded
- Seal Material = Silicone
- Seal Color = White
- Used With = Mating with Tab Housing

Contact Features:

- Contact Type = Socket
- Multiple Contact Types = Without

Packaging Features:

- Packaging Method = Box/Carton
- Packaging Quantity = 230

Other:

- Brand = TE Connectivity
- Comment = IP67,IP69K(With cover)

Corporate Information

- About TE
- Investors
- News Room
- Supplier Portal
- Careers
- Terms & Conditions
- Privacy Policy
- AODA Accessibility Policy
- AODA Multi-Year Accessibility Plan

Quick Links

- Distributor Inventory
- Product Cross Reference
- Documents & Drawings
- Product Compliance Support Center
- Site Map

Customer Support

- Email or Chat With Us
- Find a Phone Number
- Knowledge Base
- Manage Your Account

Keep Me Informed

