


MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



✓ Active

[PRODUCT DRAWING](#)
English

[3D PDF](#)

TE CONNECTIVITY (TE) 32P AMPMODU II PIN HDR.

AMPMODU | AMPMODU Headers

3-826632-2

TE Internal Number: 3-826632-2

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **64**

Header Type **Breakaway**

Product Drawings

AMPMODU II STIFTLEISTE ZWEIREIHIG

PDF
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

3D PDF

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Vertical

Connector Type

Header

Row-to-Row Spacing

2.54 mm [.1 in]

Stabilizers

Without

Strain Relief

Without

Board Standoff	Without
Profile	Standard
Product Type	Connector
Gasket	Without
<hr/>	
Configuration Features	Number of Positions 64
	Number of Rows 2
	Keyed No
	Selectively Loaded No
<hr/>	
Electrical Characteristics	Dielectric Withstanding Voltage 1000 V
<hr/>	
Body Features	Header Type Breakaway
	Post Size .63 mm [.024 in]
<hr/>	
Contact Features	Contact Protection Without
	Contact Shape Square
	Contact Type Pin
	Contact Base Material Phosphor Bronze
	Solder Tail Contact Plating Material Tin
	Contact Mating Area Plating Thickness (µm) .8
	Contact Mating Area Plating Material Gold
	Contact Current Rating (A) 5
<hr/>	
Termination Features	Termination Post Length 3.2 mm [.1259 in]
	Termination End Plating Material Tin
	Termination End Plating Thickness (µm) 3
	Termination Method to PC Board Through Hole
<hr/>	
Mechanical Attachment	PCB Mounting Style Through Hole
	PCB Mount Retention Without
	Panel Mount Retention Without
	Mating Alignment Without
	Mating Connector Lock Without
<hr/>	
Housing Features	Centerline 2.54 mm [.1 in]
	Housing Color Green

Housing Color

Green

Housing Material

PBT GV

Dimensions	Mating Post Length	6.7 mm [.264 in]
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
	High Temperature Housing	No
Operation/Application	High Speed Serial Data Connector	No
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	150
	Packaging Method	Carton
Product Compliance	Statement of Compliance PDF	

[VIEW ALL PRODUCT COMPLIANCE](#)