




MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE) 36P MOD2 STIFT LEI AMPMODU | AMPMODU Headers

3-826925-6
TE Internal Number: 3-826925-6

Always EU RoHS/ELV Compliant
Applies To **Printed Circuit Board**

Connector Style **Plug**
Centerline **2.54 mm [.1 in]**
Number of Positions **72**
Header Type **Breakaway**

Product Drawings

AMPMODU II STIFTLEISTE ZWEIREIHIG
PDF
English

CAD Files

Customer View Model
2D_DXF.ZIP
English

Customer View Model
3D_IGS.ZIP
English

Customer View Model
3D_STP.ZIP
English

3D PDF
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To	Printed Circuit Board
Connector Style	Plug
PCB Mounting Orientation	Vertical
Connector Type	Header
Row-to-Row Spacing	2.54 mm [.1 in]
Stabilizers	Without
Strain Relief	Without

	Board Standoff	Without
	Profile	Standard
	Product Type	Connector
	Gasket	Without
Configuration Features	Number of Positions	72
	Number of Rows	2
	Keyed	No
	Selectively Loaded	No
Electrical Characteristics	Dielectric Withstanding Voltage	1000 V
Body Features	Header Type	Breakaway
	Post Size	.63 mm [.024 in]
Contact Features	Contact Protection	Without
	Contact Shape	Square
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Tin
	Contact Mating Area Plating Thickness (µm)	2
	Contact Mating Area Plating Material	Tin
	Contact Current Rating (A)	5
Termination Features	Termination Post Length	3.2 mm [.1259 in]
	Termination End Plating Material	Tin
	Termination End Plating Thickness (µm)	2
	Termination Method to PC Board	Through Hole
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	Without
	Mating Connector Lock	Without
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Green

Housing Color	Green
Housing Material	PBT GV

Dimensions	Mating Post Length	6.7 mm [.264 in]
------------	--------------------	---------------------------

Usage Conditions	Operating Temperature Range (°C)	-65 – 105
	High Temperature Housing	No

Operation/Application	High Speed Serial Data Connector	No
-----------------------	----------------------------------	-----------

Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------

Packaging Features	Packaging Quantity	150
	Packaging Method	Box

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES	SURFACE MOUNT RESISTORS	RIBBON CABLE CONNECTORS	RECTANGULAR POWER CONNECTORS
<p>36P MOD2 STIFT LEI 3-826953-6</p> <p> Save to List</p> <p> Find Similar Products</p>	<p>CRG0603 1% 18R CRG0603F18R</p> <p> Save to List</p> <p> Find Similar Products</p>	<p>IDC LOW PRO HDR 14P RA BLUE 2-1761605-5</p> <p> Save to List</p> <p> Find Similar Products</p>	<p>06P MICRO MNL ASSY R/A HDR LF 3-794618-6</p> <p> Save to List</p> <p> Find Similar Products</p>