



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)  
**MOD 4 REC.HSG 2X30P**  
AMP | AMPMODU IV/V

3-925370-0  
TE Internal Number: 3-925370-0

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [ .1 in ]**

Number of Positions **60**

Number of Rows **2**

Row-to-Row Spacing **2.54 mm [ .1 in ]**

Color **Green**

Product Drawings

[AMPMODU IV GEHAEUSE, EINREIHIG Housing, Single Row](#)  
PDF  
English

CAD Files

[Customer View Model](#)  
2D\_DXF.ZIP  
English

[3D PDF](#)  
PDF  
3D

[Customer View Model](#)  
3D\_IGS.ZIP  
English

[Customer View Model](#)  
3D\_STP.ZIP  
English

Product Specifications

Product Specification [AMPMODU Mod 1/2 Wire To Board Standard Pressure Contact Interconnection System](#)  
PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Row-to-Row Spacing **2.54 mm [ .1 in ]**

Connector Style **Receptacle**

Glow Wire Rating **Standard Part - Not Glow Wire**

Strain Relief **With**

	Connector Type	<b>Housing</b>
	Product Type	<b>Connector</b>
	Applies To	<b>Printed Circuit Board</b>
Configuration Features	Number of Positions	<b>60</b>
	Number of Rows	<b>2</b>
Electrical Characteristics	Operating Voltage	<b>250 VAC</b>
Body Features	Color	<b>Green</b>
Contact Features	Contact Type	<b>Socket</b>
Termination Features	Termination Method to Wire/Cable	<b>Crimp</b>
Mechanical Attachment	Mating Retention	<b>With</b>
	Mating Retention Type	<b>Lock</b>
	Mating Connector Lock	<b>Without</b>
	Mating Alignment	<b>Without</b>
	Mating Alignment Type	<b>Polarization</b>
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Material	<b>Polyamide 6.6 GF</b>
	Housing Configuration	<b>Both Ends Closed</b>
	Housing Color	<b>Green</b>
Dimensions	Height (in)	<b>.21</b>
	Length (in)	<b>4.99</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
Operation/Application	For Use With	<b>AMPMODU Mod II .025 inch Headers</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
Packaging Features	Packaging Quantity	<b>500</b>
	Packaging Method	<b>Carton</b>

Statement of Compliance

PDF

[VIEW ALL PRODUCT COMPLIANCE](#)