

## Plug-in bridge - FBS 5-4 - 3030145

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in bridge, pitch: 4.2 mm, number of positions: 5, color: red

RoHS

### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 STK                                                                                                   |
| Minimum order quantity               | 50 STK                                                                                                  |
| GTIN                                 | <br>4 017918 188481 |
| GTIN                                 | 4017918188481                                                                                           |
| Weight per Piece (excluding packing) | 3.060 g                                                                                                 |
| Custom tariff number                 | 85389099                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Technical data

|                                        |                                                                                                                                                                                                             |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Color                                  | red                                                                                                                                                                                                         |
| Material                               | Copper                                                                                                                                                                                                      |
| Number of positions                    | 5                                                                                                                                                                                                           |
| Pitch                                  | 4.2 mm                                                                                                                                                                                                      |
| Flammability rating according to UL 94 | V0                                                                                                                                                                                                          |
| Maximum load current                   | 17.5 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |

### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|

## Plug-in bridge - FBS 5-4 - 3030145

### Technical data

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141199 |
| eCl@ss 4.1 | 27141199 |
| eCl@ss 5.0 | 27141140 |
| eCl@ss 5.1 | 27141140 |
| eCl@ss 6.0 | 27141140 |
| eCl@ss 7.0 | 27141140 |
| eCl@ss 8.0 | 27141140 |
| eCl@ss 9.0 | 27141140 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000489 |
| ETIM 3.0 | EC000489 |
| ETIM 4.0 | EC000489 |
| ETIM 5.0 | EC000489 |
| ETIM 6.0 | EC000489 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211829 |
| UNSPSC 7.0901 | 39121426 |
| UNSPSC 11     | 39121426 |
| UNSPSC 12.01  | 39121426 |
| UNSPSC 13.2   | 39121426 |

### Approvals

#### Approvals

---

Approvals

EAC

---

Ex Approvals

## Plug-in bridge - FBS 5-4 - 3030145

### Approvals

---

#### Approval details

|     |                                                                                   |               |
|-----|-----------------------------------------------------------------------------------|---------------|
| EAC |  | EAC-Zulassung |
|-----|-----------------------------------------------------------------------------------|---------------|

### Accessories

#### Accessories

#### Cutting tools

Front cutter - CUTFOX-FBS - 1212124



Cutting tool, for separating individual jumper bars from FBS ... plug-in bridges and EB ... insertion bridges