

- High density DIP sockets and strips for devices featuring .070" lead spacing.
- Hi-Rel, 4-finger #30 clip is rated at 3 amps. See page 208 for details.
- Solder tail is MM# 1802 receptacle (see page 138 for details). Wraposts are MM# 1702-2 or 1703-3 pins. See page 162 for details.

Total number of pins				Quantity per tube	<div style="border: 1px solid black; border-radius: 50%; padding: 5px; display: inline-block;"> XX=Plating Code See Below </div>			<div style="border: 1px solid green; padding: 5px; display: inline-block;"> Ordering Information For RoHS compliance, select ◇ plating code. For the all gold option (XX=13) also change part number from XX7-XX-XXX-41-00X000 to XX7-13-XXX-41-00X100 </div>			<div style="border: 1px solid green; padding: 5px; display: inline-block;"> RoHS 2002/95/EC </div>		
	A	B	C		Solder Tail	2 Level Wrapost L = .370	3 Level Wrapost L = .510						
OPEN FRAME DIP SOCKET													
16	0.572	0.3	0.39	35	117-XX-316-41-005000	127-XX-316-41-002000	127-XX-316-41-003000						
28	0.992	0.4	0.49	20	117-XX-428-41-005000	127-XX-428-41-002000	127-XX-428-41-003000						
30	1.062	0.4	0.49	18	117-XX-430-41-005000	127-XX-430-41-002000	127-XX-430-41-003000						
48	1.692	0.4	0.49	12	117-XX-448-41-005000	127-XX-448-41-002000	127-XX-448-41-003000						
20	0.712	0.6	0.69	28	117-XX-620-41-005000	127-XX-620-41-002000	127-XX-620-41-003000						
28	0.992	0.6	0.69	20	117-XX-628-41-005000	127-XX-628-41-002000	127-XX-628-41-003000						
40	1.412	0.6	0.69	14	117-XX-640-41-005000	127-XX-640-41-002000	127-XX-640-41-003000						
42	1.482	0.6	0.69	13	117-XX-642-41-005000	127-XX-642-41-002000	127-XX-642-41-003000						
48	1.692	0.6	0.69	12	117-XX-648-41-005000	127-XX-648-41-002000	127-XX-648-41-003000						
52	1.832	0.6	0.69	11	117-XX-652-41-005000	127-XX-652-41-002000	127-XX-652-41-003000						
56	1.972	0.6	0.69	10	117-XX-656-41-005000	127-XX-656-41-002000	127-XX-656-41-003000						
64	2.252	0.6	0.69	9	117-XX-664-41-005000	127-XX-664-41-002000	127-XX-664-41-003000						
68	2.392	0.6	0.69	8	117-XX-668-41-005000	127-XX-668-41-002000	127-XX-668-41-003000						
64	2.252	0.75	0.84	8	117-XX-764-41-005000	127-XX-764-41-002000	127-XX-764-41-003000						
CLOSED FRAME DIP SOCKET													
64	2.252	0.75	0.84	8	217-XX-764-41-005000	227-XX-764-41-002000	227-XX-764-41-003000						
SINGLE ROW STRIP SOCKET													
If desired, we will supply any length up to 21 pins.													
21	1.482				317-XX-121-41-005000	327-XX-121-41-002000	327-XX-121-41-003000						
					SPECIFY PLATING CODE XX=	13◇	93			43◇			
					Sleeve (Pin)	10µ" Au	200µ" Sn/Pb			200µ" Sn			
					Contact (Clip)	30µ" Au	30µ" Au			30µ" Au			