

## Plug-in bridge - FBS 2-3,5 GY - 3213153

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in bridge, pitch: 3.5 mm, number of positions: 2, color: gray

The figure shows the red version

### Why buy this product

- ✓ The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

RoHS

### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 STK                                                                                                   |
| Minimum order quantity               | 50 STK                                                                                                  |
| GTIN                                 | <br>4 046356 549240 |
| GTIN                                 | 4046356549240                                                                                           |
| Weight per Piece (excluding packing) | 1.000 g                                                                                                 |
| Custom tariff number                 | 85389099                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Technical data

|                                        |                                                                                                                                                                                                             |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Color                                  | gray                                                                                                                                                                                                        |
| Material                               | Copper                                                                                                                                                                                                      |
| Number of positions                    | 2                                                                                                                                                                                                           |
| Pitch                                  | 3.5 mm                                                                                                                                                                                                      |
| Flammability rating according to UL 94 | V0                                                                                                                                                                                                          |
| Maximum load current                   | 17.5 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |

## Plug-in bridge - FBS 2-3,5 GY - 3213153

### Technical data

#### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141111 |
| eCl@ss 4.1 | 27141111 |
| eCl@ss 5.0 | 27141133 |
| eCl@ss 5.1 | 27141133 |
| eCl@ss 6.0 | 27141133 |
| eCl@ss 7.0 | 27141133 |
| eCl@ss 8.0 | 27141140 |
| eCl@ss 9.0 | 27141140 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000886 |
| ETIM 4.0 | EC000489 |
| ETIM 5.0 | EC000489 |
| ETIM 6.0 | EC000489 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211829 |
| UNSPSC 7.0901 | 39121426 |
| UNSPSC 11     | 39121426 |
| UNSPSC 12.01  | 39121426 |
| UNSPSC 13.2   | 39121426 |

### Approvals

#### Approvals

---

Approvals

EAC

---

# Plug-in bridge - FBS 2-3,5 GY - 3213153

## Approvals

Ex Approvals

---

### Approval details

|     |                                                                                   |               |
|-----|-----------------------------------------------------------------------------------|---------------|
| EAC |  | EAC-Zulassung |
|-----|-----------------------------------------------------------------------------------|---------------|