

C-RC 240/M16 DIN

Order No.: 3240136



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3240136>

Ring cable lug, non-insulated, 240 mm², M16

Commercial data

GTIN (EAN)	 4 046356 453530
Note	Made-to-order
sales group	B282
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 315 (CL2-2011)

Product notes

WEEE/RoHS-compliant since:
09/24/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data


General

Length (b)	75 mm
Width (a)	38 mm
Color	silver
Ambient temperature (operation)	110 °C
Material	Copper

Length of insulation sleeve (c)	32 mm
Inner dimension of the insulating collar (d)	23.5 mm
Distance between the center and the insulation sleeve (e)	24 mm
Inner diameter (f)	17 mm
Material thickness (g)	4 mm

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;