

## Cable tie - WT-HT HF 3,6X140 BK - 3240783

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

Image shows WT-HT HF 4.8x200 BK version



## **Key Commercial Data**

Packing unit	1 STK
Minimum order quantity	100 STK
GTIN	4 046356 705011
GTIN	4046356705011
Weight per Piece (excluding packing)	0.680 g
Custom tariff number	39269097
Country of origin	Croatia

## Technical data

### **Dimensions**

Length (b)	140 mm
Width (a)	3.6 mm
Cable diameter	2 mm 35 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C 125 °C
Ambient temperature (assembly)	-10 °C 60 °C
Optimum ambient temperature (storage/transport)	23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water



# Cable tie - WT-HT HF 3,6X140 BK - 3240783

## Technical data

## Ambient conditions

	is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.
Short-term temperature	145 °C

## General

Color	black
Туре	Internal teeth
Components	free from silicone and halogen
Flammability rating according to UL 94	V2
Material	PA 6.6

## Standards and Regulations

Flammability rating according to UL 94	V2

## Classifications

## eCl@ss

eCl@ss 4.0	27140702
eCl@ss 4.1	27140702
eCl@ss 5.0	27140702
eCl@ss 5.1	27140702
eCl@ss 6.0	27140702
eCl@ss 7.0	27140702
eCl@ss 8.0	27140702
eCl@ss 9.0	27140702

### **ETIM**

ETIM 3.0	EC000046
ETIM 4.0	EC000046
ETIM 5.0	EC000046
ETIM 6.0	EC000046

## UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703



# Cable tie - WT-HT HF 3,6X140 BK - 3240783

## Classifications

**UNSPSC** 

UNSPSC 13.2 27121703

### Accessories

Accessories

Universal tools

Cable tie tool - UNIFOX-CT 4,8 - 1212475



Cable binder pliers, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

Cable tie tool - UNIFOX-CT 4,8P - 1212609



Cable binder pliers, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com