

Screw connection - WP-GT BRASS PG16 - 3241026

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland made from brass with Pg thread, rotatable, IP40 protection

The figure shows the WP-GT
BRASS M10 version

RoHS

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
GTIN	 4 046356 711623
GTIN	4046356711623
Custom tariff number	74122000
Country of origin	Germany

Technical data

Dimensions

Width (a)	29 mm
Height	32 mm
Wrench size	27.00 mm
Outside diameter	21.00 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 250 °C
Degree of protection	IP40

General

Color	Brass
-------	-------

Screw connection - WP-GT BRASS PG16 - 3241026

Technical data

General

Design	Rotatable
Type	Outer thread
Components	Halogen-free
Material	Brass

Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	21132007
eCl@ss 5.1	21132007
eCl@ss 6.0	21132007
eCl@ss 7.0	27439210
eCl@ss 8.0	27439203
eCl@ss 9.0	27430310

ETIM

ETIM 3.0	EC000519
ETIM 4.0	EC000519
ETIM 5.0	EC001180
ETIM 6.0	EC001180

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	40141734

Approvals

Approvals

Approvals

VDE Zeichengenehmigung

Screw connection - WP-GT BRASS PG16 - 3241026

Approvals

Ex Approvals

Approval details

VDE Zeichengenehmigung



<http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx>

Accessories

Accessories

Corrugated pipe

Protective hose - WP-STEEL ZC 21 - 3240699



Protective hose in galvanized steel

Protective hose - WP-STEEL S 21 - 3240688



Protective hose in stainless steel

Mounting material

Protective hose fixing bracket - WP-BASE A PG16 - 3241079



Fixing bracket for protective sleeves, fixed with two screws