

PART NUMBER: 336TTA160M



AXIAL LEAD

Parts are RoHS compliant

Date code when parts became RoHS: 14

FEATURES

low cost

Capacitance: 33 uF

Dissipation Factor: 0.2 Max at 120 Hz and 20°C

Temperature Range: -25°C to +85°C

ESR: 10.048 Ohms Max at 20°C and 120 Hz

Impedance: N/A

Leakage Current: .1CV+40uA

568 uA after 1 Minute

Load Life: 2000 hours at 85°C with 100 % of rated voltage and with 0 % of rated ripple current

Capacitance Change: ≤20% of initial measured value

Dissipation Factor: ≤200% of maximum specified value

Leakage Current: ≤100% of maximum specified value

APPLICATIONS

General purpose, filtering, bypass, coupling

Tolerance: -20 % , +20 %

WVDC: 160 Volts DC

SVDC: 200 Volts DC

Ripple Current: 170 mA at 120 Hz and 85°C

Impedance Ratios:

-25°C/20°C - 4

-40°C/20°C - 15

Ripple Current Multipliers

Frequency Multipliers:

50 Hz	120 Hz	400 Hz	1 kHz	10 kHz	100 kHz
0.85	1	1	1.15	1.2	1.2

Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
1.8	1.7	1.4	1.6	1	1	0	0

PHYSICAL DIMENSIONS

Diameter (D): 13 mm + 0.8 mm

Length (L): 26 mm + 2 mm

Lead Wire Width (R): 0.6 mm +/- 0.05 mm

Lead Length (LL): 35 mm +/- MIN mm

Lead Finish: Matte Tin

Coating: Blue PET sleeving

