



Part Number: 39126

Hook-Up/Lead Wire PPO, 600V, 105°C AWM Style 11032, (1) 26 AWG (7x34)
TC, PPO, 600V, 105°C

Product Description

One 26 AWG stranded (7x34) tinned copper conductor, polyphenylene oxide (PPO) insulation.

Technical Specifications

Product Overview

Suitable Applications:	Electrical panel builders, Electrical/electronic manufacturers, Appliance manufacturers, Furniture, Computer manufacturers, Automotive companies and their sub-suppliers
------------------------	--

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
26	7x34	TC - Tinned Copper	1

Conductor Count:	1
AWG Size:	26

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PPO - Polyphenylene Oxide	0.043 in	0.012 in

Construction and Dimensions

Stranding

Lay Length
AWM 11028 mm

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
37.3 Ohm/1000ft

Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	6.5 A

Voltage

UL Voltage Rating
600 V

Temperature Range

UL Temp Rating:	105°C
Operating Temp Range:	-40°C To +105°C Dry

Mechanical Characteristics

Bulk Cable Weight:	1.4 lbs/1000ft
--------------------	----------------

Standards

UL AWM Style:	AWM 11028
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2011-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
------------------	------

Part Number

Plenum (Y/N):	No
---------------	----

Variants

Item #	Color	Footnote
39126 010100	BLACK	C
39126 0101000	BLACK	C
39126 0105000	BLACK	C Z
39126 013100	BLUE, DARK	C
39126 0131000	BLUE, DARK	C
39126 0135000	BLUE, DARK	C Z
39126 0035000	BLUE, LIGHT	C Z
39126 001100	BROWN	C
39126 0011000	BROWN	C
39126 0015000	BROWN	C Z
39126 008100	GRAY	C
39126 0081000	GRAY	C
39126 0085000	GRAY	C Z
39126 005100	GREEN, DARK	C
39126 0051000	GREEN, DARK	C
39126 0055000	GREEN, DARK	C Z
39126 0031000	ORANGE	C
39126 002100	RED	C
39126 0021000	RED	C
39126 0025000	RED	C Z
39126 007100	VIOLET	C
39126 0071000	VIOLET	C
39126 0075000	VIOLET	C Z
39126 009100	WHITE	C
39126 0091000	WHITE	C
39126 0095000	WHITE	C Z
39126 004100	YELLOW	C
39126 0041000	YELLOW	C
39126 0045000	YELLOW	C Z

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Product Notes

Notes:	Halogen-free.
--------	---------------

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS(Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be instock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.