CATALOG 3DAFP SAFETY ORGANIZATIONS RELIABILITY SPECIFICATIONS: ECN # APPRVD. DATE STORAGE TEMPERATURE: -40°C TO +85°C THIS FILTER HAS NOT YET BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED HUMIDITY: 21 DAYS @ 40°C 95% RH. BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED CURRENT OVERLOAD TEST: 6 TIMES In FOR IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS 8 ZECONDZ HAVE NOT YET BEEN MET: TEST SPECIFICATIONS: ENGINEERING SAMPLE O UL RECOGNIZED: UL 1283 CSA CERTIFIED: CSA 22.2, # 8 INDUCTANCE: 1.45 mH NOMINAL VDE APPROVED: VDE 565-3 CAPACITANCE: (MEASURED @ 1KHz, 0.250VAC MAX., 25°C±1°C) LINE TO GROUND: (0.005 µF ±20%) OPERATING SPECIFICATIONS (0.100 µF ±20%) LINE TO LINE: TBD DISCHARGE RESISTOR: 3.3 Ma LINE CURRENT/VOLTAGE: 3 AMP, 125 VDC L/G AND L/L I.R NO DISCHARGE RESISTOR: 6000M₁ (MIN.) @ 100VDC, 20°C AND 50% RH LINE FREQUENCY: RECOMMENDED RECEIVING INSPECTION HIPOT: MAXIMUM LEAKAGE CURRENT, EACH LINE TO GROUND: 0.01 mA@ 100VDC 2250VDC FOR 1 MINUTE LINE TO GROUND: LINE TO LINE: 1450VDC FOR 1 MINUTE OPERATING AMBIENT TEMP. RANGE: -10°C TO +55°C @ RATED CURRENT, Ir. FILTER APPROVAL: IN AN AMBIENT, To, HIGHER THAN 55°C, THE MAXIMUM OPERATING CURRENT, Io, IS AS FOLLOWS: T = T = $\sqrt{-Q\Omega}$ = T. THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR $I_0 = I_r$ YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT. - 1.98 MAX. -1.54 MAX. -0.81 MAX. 1.575±.015 -0.138 ±.010 DA 0.537 Series ±.020 0.380 MAX. 0.560 Ø 0.140±.01 ±.015 0.551 Ø 0.260 REF X 82° CSINK FOR #4 FLT HD SCR (2X) ±.010 0.520 MATES WITH MOLEX HCS-125: 03-12-1026 0.031 X .060 ±.003 WITH FEMALE 18121221/ 18121222 TERMINALS. R 0.234 (4X) $\emptyset 0.075$ (3 HOLES) 0.900 1.13 \circ MAX. \oplus 1.200 - 1.575 -0.520 PANEL CUTOUT (BACK MOUNT) 0.551 TOLERANCE ±.005 - 0.685±.015 (CENTER PIN TO PANEL) PC LAYDUT 50_-50 \(\text{(MINIMUM)}\) INSERTION $\Gamma \square ZZ$ THIRD ANGLE PROJECTION FREQUENCY 844 E. ROCKLAND RD. LIBERTYVILLE IL 60048 05 . 15 50 3 5 100 200 . 10 10 30 UNLESS OTHERWISE SPECIFIED. MHz TOLERANCE TO BE ±.025 DC LINE FILTER CDMMDNMATERIAL & FINISH: AS SUPPLIED 6 9 11 26 41 48 52 55 46 22 16 This document is proprietary to CORCOM INC. CAD FILE: G:\CD\\3ADFPO1 ond is not to be reproduced nor used for SCALE: NTS DATE: 8/2/01 dB DATE: 8/2/01 CATALOG NO. REV. DIFF 7 16 18 37 47 50 43 31 36 manufacturing purposes except on CORCOM'S 3DAFP 1 DRW. BY: ORIG: dB ELC prior written consent.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: