



SIRIUS SAFETY RELAY WITH RELAY RELEASE CIRCUITS (RC),
DC 24V, 45.0MM, SCREW TERMINAL,
RC INSTANT.: 4NO, RC DELAYED: 0, MK: 3,
8-FUNCTION SWITCH, BASIC DEVICE,
MAX. ACHIEVABLE PL TO EN13849-1: E,
MAX. ACHIEVABLE SIL TO IEC61508:3,

General technical details:

product brand name		SIRIUS
Product designation		safety relays
Design of the product		for EMERGENCY-STOP units
protection type IP / of the enclosure		IP20
Protection class IP / of the terminal		IP20
Protection against electrical shock		finger-safe
Insulation voltage / rated value	V	300
Ambient temperature		
• during storage	°C	-40 ... +80
• during operating	°C	-25 ... +60
Air pressure		
• according to SN 31205	kPa	90 ... 106
Relative humidity		
• during operating phase	%	10 ... 95
Installation altitude / at a height over sea level / maximum	m	2,000
Resistance against vibration / according to IEC 60068-2-6		5 ... 500 Hz: 0,075 mm
Resistance against shock		8g / 10 ms
Impulse voltage resistance / rated value	V	4,000
EMC emitted interference		EN 60947-5-1

Installation environment relating to EMC		This product is suitable for Class A environments only. It can cause undesired radio-frequency interference in residential environments. If this is the case, the user must take appropriate measures.
Reference code • according to DIN 40719 extended according to IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		KT F
Number of sensor inputs • 1-channel or 2-channel		1
Design of the cascading		cascading or in-service switching
Type of the safety-related wiring / of the inputs		single-channel and two-channel
Product feature / transverse contact-secure		Yes
Safety Integrity Level (SIL) • according to IEC 61508		SIL3
SIL claim limit (for a subsystem) / according to EN 62061		3
Performance Level (PL) • according to EN ISO 13849-1		e
Category / according to EN 954-1		4
Category / according to EN ISO 13849-1		4
Hardware fault tolerance / according to IEC 61508		1
Safety device type / according to IEC 61508-2		Type B
PFHD / with high demand rate / according to EN 62061	1/h	0.78E-8
Average probability of failure on demand (PFDavg) / with low demand rate / according to IEC 61508	1/y	0.15E-4
T1 value / for proof test interval or service life / according to IEC 61508	a	20
Number of outputs / as contact-affected switching element • as NC contact / for reporting function / instantaneous switching • as NO contact / safety-related / instantaneous switching • as NO contact / safety-related / delayed switching		1 4 0
Number of outputs / as contact-less semiconductor switching element • safety-related • delayed switching • non-delayed • for reporting function • delayed switching • non-delayed		0 0 0 2
Stop category / according to DIN EN 60204-1		0

General technical details:

Design of the input		
• cascading-input/functional switching		Yes
• feedback input		Yes
• start input		Yes
Design of the electrical connection / jumper socket		Yes
Operating cycles / maximum	1/h	2,000
Switching capacity current		
• of semiconductor outputs		
• for signaling function / for DC-13 / at 24 V	A	0.5
• of NO contacts of relay outputs		
• at DC-13		
• at 24 V	A	4
• at 115 V	A	0.2
• at 230 V	A	0.1
• at AC-15		
• at 24 V	A	4
• at 115 V	A	4
• at 230 V	A	4
• of NC contacts of relay outputs		
• at DC-13		
• at 24 V	A	2
• at 115 V	A	0.2
• at 230 V	A	0.1
• at AC-15		
• at 24 V	A	4
• at 115 V	A	3
• at 230 V	A	3
Thermal current / of the contact-affected switching element / maximum	A	5
Electrical operating cycles as operating time / typical		100,000
Mechanical operating cycles as operating time / typical		10,000,000
Design of the fuse link / for short-circuit protection of the NO contacts of the relay outputs / required		gL/gG: 4 A, or quick: 6 A
Resistance to direct current / of the cable / maximum	Ω	1,000
Cable length / between sensor and electronic evaluation device / with Cu 1.5 mm² and 150 nF/km / maximum	m	2,000
Make time / with automatic start		
• typical	ms	50
• for DC / maximum	ms	100
• for AC / maximum	ms	100
Make time / with automatic start / after mains power cut		

• typical	ms	8,000
• maximum	ms	8,200
Make time / with monitored start		
• maximum	ms	100
• typical	ms	50
Backslide delay time / after opening of the safety circuits / typical	ms	50
Backslide delay time / at mains power cut		
• typical	ms	75
• maximum	ms	125
Recovery time / after opening of the safety circuits / typical	ms	250
Recovery time / after mains power cut / typical	s	8.2
Pulse duration		
• of the sensor input / minimum	ms	30
• of the ON pushbutton input / minimum	s	0.2
• of the cascading-entrance / minimum	s	0.2

Control circuit:

Voltage type / of control feed voltage		DC
Control supply voltage / 1 / for DC / rated value	V	24
operating range factor control supply voltage rated value / of the magnet coil		
• for DC		0.85 ... 1.2

Installation/mounting/dimensions:

mounting position		any
Mounting type		screw and snap-on mounting
Width	mm	45
Height	mm	138.5
Depth	mm	120

Connections:

Design of the electrical connection		screw-type terminals
Type of the connectable conductor cross-section		
• solid		1x (0.5 ... 4.0 mm²), 2x (0.5 ... 2.5 mm²)
• finely stranded		
• with wire end processing		1x (0.5 ... 2.5 mm²), 2x (0.5 ... 1.5 mm²)
Type of the connectable conductor cross-sections / for AWG conductors		
• solid		2x (20 ... 14)
• stranded		2x (20 ... 14)

Product Function:**Product function**

- light barrier monitoring
- standstill monitoring
- protective door monitoring
- automatic start
- magnetic switch monitoring Normally closed contact-Normally open contact
- rotation speed monitoring
- laser scanner monitoring
- monitored start-up
- light grid monitoring
- magnetic switch monitoring Normally closed contact-Normally closed contact
- emergency stop function
- step mat monitoring

Yes
No
Yes
Yes
Yes
No
Yes
Yes
Yes
Yes
Yes
Yes

Suitability for interaction / pressing control

No

Acceptability for application

- monitoring of floating sensors
- monitoring of non-floating sensors
- safety cut-out switch
- position switch monitoring
- EMERGENCY-OFF circuit monitoring
- valve monitoring
- tactile sensor monitoring
- magnetically operated switches monitoring
- safety-related circuits

Yes
Yes
Yes
Yes
Yes
No
Yes
Yes
Yes

Certificates/approvals:**Verification of suitability**

- TÜV (German technical inspectorate) certificate
- UL-registration
- BG BIA certificate

UL, CSA, EN 60204-1, EN ISO 12100, EN 954-1, IEC 61508
Yes
Yes
Yes

General Product Approval			EMC	Functional Safety / Safety of Machinery	
 CCC	 CSA	 EAC	 UL	 C-TICK	 VDE
Declaration of Conformity	Test Certificates	other			
 EG-Konf.	Special Test Certificate	Environmental Confirmations			

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:



<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3TK2826-1BB40/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3TK2826-1BB40



last change:

Jul 28, 2014