



RECOMMENDED HOLE LAYOUT

1. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS.
-  BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
-  .000100--.000200 MATTE TIN--LEAD OVER .000050 NICKEL
-  .000100--.000200 BRIGHT TIN OVER .000050 NICKEL.
-  PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
-  HOUSING MATERIAL: FLAME RETARDANT THERMOPLASTIC; COLOR--BLACK.
-  POSTS: PHOS BRONZE
-  .000100--.000200 MATTE TIN OVER .000050 NICKEL
-  OBSOLETE PARTS: OBSOLETE CIS STREAMLINER PER D.RENAUD/D.SINISI

	3.984	3.900	39	40	9-10332-10
OBSOLETE	3.984	3.900	38	39	9-10330-9
OBSOLETE	3.784	3.700	37	38	9-10326-8
OBSOLETE	3.684	3.600	36	37	9-10326-7
	3.584	3.500	35	36	9-10326-6
OBSOLETE	3.484	3.400	34	35	9-10326-5
OBSOLETE	3.384	3.300	33	34	9-10326-4
	3.284	3.200	32	33	9-10326-3
OBSOLETE	3.184	3.100	31	32	9-10326-2
OBSOLETE	3.084	3.000	30	31	9-10326-1
OBSOLETE	2.984	2.900	29	30	9-10325-9
OBSOLETE	2.884	2.800	28	29	9-10325-8
OBSOLETE	2.784	2.700	27	28	9-10325-7
OBSOLETE	2.684	2.600	26	27	9-10325-6
OBSOLETE	2.584	2.500	25	26	9-10325-5
OBSOLETE	2.484	2.400	24	25	9-10325-4
OBSOLETE	2.384	2.300	23	24	9-10325-3
OBSOLETE	2.284	2.200	22	23	9-10325-2
OBSOLETE	2.184	2.100	21	22	9-10325-1
OBSOLETE	2.084	2.000	20	21	9-10324-9
OBSOLETE	1.984	1.900	19	20	9-10323-10
OBSOLETE	1.884	1.800	18	19	9-10323-9
OBSOLETE	1.784	1.700	17	18	9-10323-8
OBSOLETE	1.684	1.600	16	17	9-10323-7
OBSOLETE	1.584	1.500	15	16	9-10323-6
OBSOLETE	1.484	1.400	14	15	9-10323-5
OBSOLETE	1.384	1.300	13	14	9-10323-4
OBSOLETE	1.284	1.200	12	13	9-10323-3
OBSOLETE	1.184	1.100	11	12	9-10323-2
OBSOLETE	1.084	1.000	10	11	9-10323-1
	.984	.900	9	10	9-10322-10
OBSOLETE	.884	.800	8	9	9-10322-9
OBSOLETE	.784	.700	7	8	9-10322-8
OBSOLETE	.684	.600	6	7	9-10322-7
OBSOLETE	.584	.500	5	6	9-10322-6
	.484	.400	4	5	9-10322-5
	.384	.300	3	4	9-10322-4
OBSOLETE	.284	.200	2	3	9-10322-3
OBSOLETE	.184	.100	1	2	9-10322-2
OBSOLETE	.084	—	1	1	9-10322-1

		1984.100	1	2	4-103323-2
		3.984.9,300	39	40	4-103323-1
		3.984.9,300	39	40	4-103323-0
	OBSELETE	3.884.8,300	38	39	3-103323-9
	OBSELETE	3.784.7,300	37	38	3-103323-8
	OBSELETE	3.684.6,300	36	37	3-103323-7
	SUPERSEDED	3.584.5,300	35	36	3-103323-6
	OBSELETE	3.484.4,300	34	35	3-103323-5
	OBSELETE	3.384.3,300	33	34	3-103323-4
	OBSELETE	3.284.2,300	32	33	3-103323-3
	OBSELETE	3.184.1,300	31	32	3-103323-2
	OBSELETE	3.084.0,300	30	31	3-103323-1
	OBSELETE	2.984.2,900	29	30	3-103323-0
	OBSELETE	2.884.2,800	28	29	2-103323-9
	OBSELETE	2.784.2,700	27	28	2-103323-8
	OBSELETE	2.684.2,600	26	27	2-103323-7
	OBSELETE	2.584.2,500	25	26	2-103323-6
	OBSELETE	2.484.2,400	24	25	2-103323-5
	OBSELETE	2.384.2,300	23	24	2-103323-4
	OBSELETE	2.284.2,200	22	23	2-103323-3
	OBSELETE	2.184.2,100	21	22	2-103323-2
	OBSELETE	2.084.2,000	20	21	2-103323-1
		1.984.1,900	19	20	2-103323-0
	OBSELETE	1.884.1,800	18	19	1-103323-9
	OBSELETE	1.784.1,700	17	18	1-103323-8
	OBSELETE	1.684.1,600	16	17	1-103323-7
		1.584.1,500	15	16	1-103323-6
	OBSELETE	1.484.1,400	14	15	1-103323-5
	OBSELETE	1.384.1,300	13	14	1-103323-4
	OBSELETE	1.284.1,200	12	13	1-103323-3
	OBSELETE	1.184.1,100	11	12	1-103323-2
	OBSELETE	1.084.1,000	10	11	1-103323-1
		984.900	9	10	1-103323-0
	OBSELETE	884.800	8	9	103323-9
		784.700	7	8	103323-8
		684.600	6	7	103323-7
		584.500	5	6	103323-6
	SUPERSEDED	484.400	4	5	103323-5
	SUPERSEDED	384.300	3	4	103323-4
		284.200	2	3	103323-3
		184.100	1	2	103323-2
	OBSELETE	.084	—	1	103323-1

PLATING	C	B	A	NO OF POSN	PART NUMBER		PLATING	C	B	A	NO OF POSN	PART NUMBER
---------	---	---	---	------------	-------------	--	---------	---	---	---	------------	-------------

[illegible]