



Tyco Electronics
Authorized Distributor

通用继电器 (接上页)

尺寸 (mm)

图 14 - T9A 系列




图 15 - T92 系列




图 16 - PRD 系列




图 17 - S86R, S87R 系列




图	触点排列	线圈电压	线圈电流 (mA)	触点额定值 (A)	端子类型 英寸 (mm)	其它特点	品牌名	Digi-Key 零件编号	单价				Tyco Electronics 零件编号
—	DPDT	24 VDC	21.8	8	PC 安装	防焊剂	Schrack	PB943-ND	5.04	4.41	3.99	3.15	RP420024
	DPDT	24 VDC	21.8	8	PC 安装	防焊剂	Schrack	PB944-ND	5.04	4.41	3.99	3.15	RP421024
	SPDT	12 VDC	44.4	16	PC 安装	防焊剂	Schrack	PB945-ND	5.04	4.41	3.99	3.15	RP710012
	SPDT	24 VDC	21.8	16	PC 安装	防焊剂	Schrack	PB946-ND	5.04	4.41	3.99	3.15	RP710024
	SPDT	12 VDC	44.4	12	PC 安装	密封外壳	Schrack	PB947-ND	4.49	3.93	3.56	2.81	RP818012
	SPDT	24 VDC	21.8	12	PC 安装	密封外壳	Schrack	PB948-ND	4.49	3.93	3.56	2.81	RP818024
	DPDT	12 VDC	44.4	8	PC 安装	密封外壳	Schrack	PB949-ND	5.04	4.41	3.99	3.15	RP820012
	DPDT	24 VDC	21.8	8	PC 安装	密封外壳	Schrack	PB950-ND	5.04	4.41	3.99	3.15	RP820024
	DPDT	12 VDC	44.4	8	PC 安装	密封外壳	Schrack	PB951-ND	5.04	4.41	3.99	3.15	RP821012
	DPDT	24 VDC	21.8	8	PC 安装	密封外壳	Schrack	PB952-ND	5.04	4.41	3.99	3.15	RP821024
KRP/KRPA/KBP 系列 - 八插端子通用继电器													
12	SPST-NO	120 VAC	17.5	20	8 引脚, 八角形	—	Potter & Brumfield	PB626-ND	64.27	56.24	50.89	40.17	KRP-3AH-120
	DPDT	110 VDC	11.5	10	8 引脚, 八角形	—	Potter & Brumfield	PB473-ND	—	68.74	—	—	KRP-11DG-110
	DPDT	120 VAC	—	10	8 引脚, 八角形	—	Potter & Brumfield	PB474-ND	65.81	57.59	52.10	41.13	KRP-11AG-120
	SPDT	120 VAC	17.5	10	8 引脚, 八角形	—	Potter & Brumfield	PB637-ND	25.03	21.91	19.82	15.65	KRPA-5AG-120
	SPDT	120 VAC	17.5	5	8 引脚, 八角形	银触点	Potter & Brumfield	PB837-ND	25.03	21.91	19.82	15.65	KRPA-5AY-120
	SPDT	24 VDC	51	10	8 引脚, 八角形	—	Potter & Brumfield	PB638-ND	22.75	19.91	18.02	14.22	KRPA-5DG-24
	SPDT	12 VDC	100	5	8 引脚, 八角形	银触点	Potter & Brumfield	PB838-ND	22.75	19.91	18.02	14.22	KRPA-5DY-12
	DPDT	12 VAC	168	10	8 引脚, 八角形	—	Potter & Brumfield	PB628-ND	16.22	14.20	12.85	10.14	KRPA-11AG-12
	DPDT	24 VAC	—	10	8 引脚, 八角形	—	Potter & Brumfield	PB167-ND	16.22	14.20	12.85	10.14	KRPA-11AG-24
	DPDT	120 VAC	—	10	8 引脚, 八角形	—	Potter & Brumfield	PB168-ND	17.35	15.19	13.74	10.85	KRPA-11AG-120
	DPDT	240 VAC	8.75	10	8 引脚, 八角形	—	Potter & Brumfield	PB629-ND	18.48	16.17	14.63	11.55	KRPA-11AG-240
	DPDT	12 VDC	100	10	8 引脚, 八角形	—	Potter & Brumfield	PB169-ND	16.22	14.20	12.85	10.14	KRPA-11DG-12
	DPDT	24 VDC	51	10	8 引脚, 八角形	—	Potter & Brumfield	PB170-ND	16.22	14.20	12.85	10.14	KRPA-11DG-24
	DPDT	48 VDC	26.6	10	8 引脚, 八角形	—	Potter & Brumfield	PB633-ND	17.35	15.19	13.74	10.85	KRPA-11DG-48
	DPDT	110 VDC	11.5	10	8 引脚, 八角形	—	Potter & Brumfield	PB476-ND	17.35	15.19	13.74	10.85	KRPA-11DG-110
	DPDT	24 VAC	84	10	8 引脚, 八角形	带指示灯	Potter & Brumfield	PB630-ND	16.78	14.68	13.29	10.49	KRPA-11AN-24
	DPDT	120 VAC	—	10	8 引脚, 八角形	带指示灯	Potter & Brumfield	PB175-ND	16.78	14.68	13.29	10.49	KRPA-11AN-120
	DPDT	240 VAC	8.75	10	8 引脚, 八角形	带指示灯	Potter & Brumfield	PB631-ND	19.06	16.68	15.09	11.91	KRPA-11AN-240
	DPDT	12 VDC	100	10	8 引脚, 八角形	带指示灯	Potter & Brumfield	PB634-ND	16.78	14.68	13.29	10.49	KRPA-11DN-12
	DPDT	24 VDC	51	10	8 引脚, 八角形	带指示灯	Potter & Brumfield	PB475-ND	16.78	14.68	13.29	10.49	KRPA-11DN-24
	DPDT	120 VAC	17.5	5	8 引脚, 八角形	银触点	Potter & Brumfield	PB632-ND	17.35	15.19	13.74	10.85	KRPA-11AY-120
	DPDT	24 VDC	51	5	8 引脚, 八角形	—	Potter & Brumfield	PB635-ND	16.22	14.20	12.85	10.14	KRPA-11DY-24
	3PDT	24 VAC	—	10	11 引脚八角形	—	Potter & Brumfield	PB171-ND	—	17.73	—	—	KRPA-14AG-24
	3PDT	120 VAC	—	10	11 引脚八角形	—	Potter & Brumfield	PB172-ND	19.06	16.68	15.09	11.91	KRPA-14AG-120
	3PDT	12 VDC	100	10	11 引脚八角形	—	Potter & Brumfield	PB173-ND	18.22	15.94	14.43	11.39	KRPA-14DG-12
	3PDT	24 VDC	51	10	11 引脚八角形	—	Potter & Brumfield	PB174-ND	18.22	15.94	14.43	11.39	KRPA-14DG-24
	3PDT	110 VDC	11.5	10	11 引脚八角形	—	Potter & Brumfield	PB673-ND	20.50	17.94	16.23	12.81	KRPA-14DG-110
	3PDT	120 VAC	—	10	11 引脚八角形	带指示灯	Potter & Brumfield	PB176-ND	19.63	17.18	15.55	12.27	KRPA-14AN-120
	3PDT	24 VDC	51	10	11 引脚八角形	带指示灯	Potter & Brumfield	PB636-ND	18.77	16.43	14.86	11.73	KRPA-14DN-24
	DPDT	120 VAC	—	10	11 引脚八角形	卡锁继电器	Potter & Brumfield	PB627-ND	213.70	186.99	169.18	133.56	KBP-11AG-120
T90 系列 - 低成本 PC 安装功率继电器 - 符合 RoHS 规范要求													
13	SPST-NO	12 VDC	77	30	PC 安装	—	Potter & Brumfield	PB104-ND	2.78	2.44	2.21	1.74	T90N1D12-12
	SPST-NO	24 VDC	36	30	PC 安装	—	Potter & Brumfield	PB105-ND	2.83	2.48	2.25	1.77	T90N1D12-24
	SPST-NO	5 VDC	185	30	PC 安装	—	Potter & Brumfield	PB106-ND	2.88	2.52	2.28	1.80	T90N5D12-5
	SPDT	12 VDC	77	20	PC 安装	—	Potter & Brumfield	PB107-ND	2.88	2.52	2.28	1.80	T90N5D12-12
	SPDT	24 VDC	36	20	PC 安装	—	Potter & Brumfield	PB108-ND	2.93	2.57	2.32	1.83	T90N5D12-24
	SPST-NO	5 VDC	185	30	PC 安装	—	Potter & Brumfield	PB109-ND	3.19	2.80	2.53	2.00	T90S1D12-5
	SPST-NO	12 VDC	77	30	PC 安装	—	Potter & Brumfield	PB110-ND	3.24	2.84	2.57	2.03	T90S1D12-12
	SPST-NO	24 VDC	36	30	PC 安装	—	Potter & Brumfield	PB111-ND	3.24	2.84	2.57	2.03	T90S1D12-24
	SPDT	5 VDC	185	20	PC 安装	—	Potter & Brumfield	PB113-ND	3.19	2.80	2.53	2.00	T90S5D12-5
	SPDT	12 VDC	77	20	PC 安装	—	Potter & Brumfield	PB114-ND	3.24	2.84	2.57	2.03	T90S5D12-12
	SPDT	24 VDC	36	20	PC 安装	—	Potter & Brumfield	PB115-ND	3.26	2.86	2.59	2.04	T90S5D12-24
	—	适用于开放式 T90 系列的防尘盖 (压入继电器)	—	—	—	—	Potter & Brumfield	PB216-ND	.86	.76	.69	.54	35C620A
T9A 系列 - 低成本工业继电器 - 符合 RoHS 规范要求													
14	SPDT	5 VDC	185	30	PC 安装	带 0.250" QC 端子	Potter & Brumfield	PB1015-ND	3.31	2.90	2.63	2.07	T9ASD22-5
	SPST-NO	12 VDC	83	30	PC 安装	—	Potter & Brumfield	PB302-ND	3.07	2.69	2.44	1.92	T9AS1D12-12
	SPST-NO	24 VDC	42	30	PC 安装	—	Potter & Brumfield	PB303-ND	3.07	2.69	2.44	1.92	T9AS1D12-24
	SPST-NO	48 VDC	20.8	30	PC 安装	—	Potter & Brumfield	PB1013-ND	3.46	3.03	2.74	2.16	T9AS1D12-48
	SPST-NO	5 VDC	185	30	PC 安装	—	Potter & Brumfield	PB1014-ND	3.00	2.63	2.38	1.88	T9AS1D12-5
	SPST-NO	12 VDC	83	30	PC 安装	带 0.250" QC 端子	Potter & Brumfield	PB304-ND	3.31	2.90	2.63	2.07	T9AS1D22-12
	SPST-NO	24 VDC	42	30	PC 安装	带 0.250" QC 端子	Potter & Brumfield	PB305-ND	3.31	2.90	2.63	2.07	T9AS1D22-24
	SPST-NO	24 VDC	42	30	.250 (6.35) QC 底座安装	—	Potter & Brumfield	PB1012-ND	3.77	3.30	2.99	2.36	T9AP1D52-24
	SPDT	12 VDC	83	20	PC 安装	—	Potter & Brumfield	PB306-ND	3.12	2.73	2.47	1.95	T9ASD12-12
	SPDT	24 VDC	42	20	PC 安装	—	Potter & Brumfield	PB307-ND	3.12	2.73	2.47	1.95	T9ASD12-24
	SPDT	12 VDC	83	20	PC 安装	带 0.250" QC 端子	Potter & Brumfield	PB308-ND	3.31	2.90	2.63	2.07	T9ASD22-12
	SPDT	24 VDC	42	20	PC 安装	带 0.250" QC 端子	Potter & Brumfield	PB309-ND	3.31	2.90	2.63	2.07	T9ASD22-24
	SPDT	12 VDC	83	20	.250 (6.35) QC 底座安装	—	Potter & Brumfield	PB310-ND	3.77	3.30	2.99	2.36	T9AP5D52-12
	SPDT	24 VDC	42	20	.250 (6.35) QC 底座安装	—	Potter & Brumfield	PB311-ND	3.77	3.30	2.99	2.36	T9AP5D52-24
T92 系列 - 带快速连接端子的功率继电器 - 密封和未密封 - 符合 RoHS 规范要求													
15	DPST-NO	12 VDC	139	30	PC 安装	密封外壳	Potter & Brumfield	PB481-ND	12.07	10.57	9.56	7.55	T92S7D12-12
	DPST-NO	24 VDC	68	30	PC 安装	密封外壳	Potter & Brumfield	PB482-ND	12.07	10.57	9.56	7.55	T92S7D12-24
	DPST-NO	240 VAC	—	30	PC 安装	密封外壳	Potter & Brumfield	PB483-ND	15.00	13.13	11.88	9.38	T92S7A12-240
	DPST-NO	12 VDC	139	30	PC 安装	非密封外壳	Potter & Brumfield	PB484-ND	11.33	9.92	8.97	7.08	T92P7D12-12
	DPST-NO	24 VDC	68	30	PC 安装	非密封外壳	Potter & Brumfield	PB485-ND	11.33	9.92	8.97	7.08	T92P7D12-24
	DPST-NO	12 VDC	139	30	.250 (6.35) QC 密封外壳	—	Potter & Brumfield	PB298-ND	12.07	10.57	9.56	7.55	T92S7D22-12
	DPST-NO	12 VDC	139	30	.250 (6.35) QC 非密封外壳	—	Potter & Brumfield	PB486-ND	11.33	9.92	8.97	7.08	T92P7D22-12
	DPST-NO	24 VDC	68	30	.250 (6.35) QC 密封外壳	—	Potter & Brumfield	PB299-ND	12.07	10.57	9.56	7.55	T92S7D22-24
	DPST-NO	24 VDC	68	30	.250 (6.35) QC 非密封外壳	—	Potter & Brumfield	PB1008-ND	11.33	9.92	8.97	7.08	T92P7D22-24
	DPST-NO	110 VDC	115	30	.250 (6.35) QC 密封外壳	—	Potter & Brumfield	PB1011-ND	13.66	11.95	10.82	8.54	T92S7D22-110
	DPST-NO	24 VAC	—	30	.250 (6.35) QC 非密封外壳	—	Potter & Brumfield	PB487-ND	11.88	10.40	9.41	7.43	T92P7A22-24
	DPST-NO	24 VAC	—	30	.250 (6.35) QC 密封外壳	—	Potter & Brumfield	PB488-ND	12.86	11.26	10.19	8.04	T92S7A22-24