



## 4-1437564-1 Product Details

[Share](#) [Print](#) [Email](#)


**4-1437564-1**

TE Internal Number: 4-1437564-1

Active

### Toggle Switches

Not EU RoHS or ELV Compliant

#### Product Highlights:

- TST (Tiny) Series
- Single Pole - Double Throw Configuration (Pole-Throw)
- Current Rating = 0.4 VA A
- Mount Style = Through-Hole
- Termination Type = Printed Circuit, Vertical

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)
[Request Sample](#)
[Find Similar Products](#)
[Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- [OUTLINE DRAWING TST71218](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Additional Product Images:

- [Dimensional Drawing](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

Feedback

### Product Features (Please use the Product Drawing for all design activity)

#### Electrical Characteristics:

- Current Rating (A) = 0.4 VA

#### Termination Features:

- Termination Type = Printed Circuit, Vertical
- Seal Type = O-Ring

#### Dimensions:

- Toggle Length (mm [in]) = 4.29 [0.169]

#### Body Features:

- Mount Style = Through-Hole
- Bushing Style = Unthreaded
- Bushing Type = Plain

#### Contact Features:

- Contact Plating = Gold over Nickel
- Contact Base Material = Copper Alloy

#### Housing Features:

- Toggle Style = Baton Short
- Process Sealed = Yes

#### Configuration Features:

- Configuration (Pole-Throw) = Single Pole - Double Throw
- Operating Function = On Off On

#### Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C

#### Other:

- Series = TST (Tiny)
- Brand = TE Connectivity

### Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

### Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

### Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

### Keep Me Informed



