



DISCRETE SOCKETS



TE CONNECTIVITY (TE)

SOCKET,MIN-SPR W/N SN-AU SER-4

MINI-SPRING SOCKETS | Series 5

4-5332070-4

TE Internal Number: 4-5332070-4

Always EU RoHS/ELV Compliant

Socket Length **3.63 mm [.143 in]**

Hole Size (Recommended) **1.83 mm [.072 in]**

Sealant **Without**

Sleeve Style **Open Bottom**

Wire/Cable Size **.326 – .518 mm² [22 – 20 AWG]**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

MINIATURE SPRING SOCKET ASSEMBLY SERIES 4

PDF
English

CAD Files

3D PDF

PDF
3D

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sleeve Style

Open Bottom

Product Type

Contact

Profile

Zero

Wire/Cable Type

Discrete Wire

Applies To

Printed Circuit Board, Wire/Cable

Body Features

Sealant

Without

Spring Material

Beryllium Copper

Sleeve Plating Material **Tin**

Sleeve Material **Copper**

Contact Features	Contact Current Rating (A)	6.5
	Contact Transmits (Typical)	Signal (Data)/Power
	Contact Spring Plating Thickness	1.27 µm [30 µin]
	Contact Base Material	Beryllium Copper
	Contact Mating Area Plating Thickness	.76 µm [30 µin]
	Socket Type	Discrete
	Contact Type	Socket
	Contact Spring Plating Material	Gold
	Contact Mating Area Plating Material	Gold

Termination Features	Termination Method to PC Board	Through Hole - Press-Fit
	Termination Method to Wire/Cable	Solder
	Insertion Method	Hand/Semi-Automatic

Dimensions	Socket Length	3.63 mm [.143 in]
	Hole Size (Recommended)	1.83 mm [.072 in]
	Wire/Cable Size	.326 – .518 mm² [22 – 20 AWG]
	Mating Pin Diameter Range	.71 – .84 mm [.028 – .033 in]
	PCB Thickness (Recommended)	.79 – 3.18 mm [.031 – .125 in]

Usage Conditions	Operating Temperature Range	-65 – 125 °C [-85 – 257 °F]
------------------	-----------------------------	--------------------------------------

Packaging Features	Packaging Quantity	2000
	Packaging Method	Bag, Loose Piece

Product Compliance [Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

DISCRETE SOCKETS 	RIBBON CABLE CONNECTORS 	DISCRETE SOCKETS 	RIBBON CABLE CONNECTORS 
--	---	--	---

SOCKET, MIN-SPR W/H SN-AU SER-5
1-5050871-0

 Save to List

 Find Similar Products

MICRO-MATCH SMD FTE
7-188275-8

 Save to List

 Find Similar Products

SOCKET, MIN-SPR W/H SN-AU SER-4
2-5332070-5

 Save to List

 Find Similar Products

040 UNIV HDR SP 4S 30DP
STD L1
102321-9

 Save to List

 Find Similar Products

