

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0040130851

Status:

Active

Description:

MiniFit Term Crp Fem chain Bs 50Au 18-24

Documents:	
Drawing (PDF)	Packaging Specification PK-5556-001 (PDF)
Product Specification PS-5556-001 (PDF)	Test Summary TS-5556-002 (PDF)
Product Specification PS-5556-002 (PDF)	RoHS Certificate of Compliance (PDF)

General	
Product Family	Crimp Terminals
Series	5556
Crimp Quality Equipment	Yes
UPC	800753839892

Physical	
Net Weight	0.130/g

Material Info	
Old Part Number	5556GS7

Reference - Drawing Numbers	
Packaging Specification	PK-5556-001
Product Specification	PS-5556-001 , PS-5556-002 , RPS-5556-004
Sales Drawing	SD-5556-006
Test Summary	TS-5556-002

EU ELV

Not Relevant

EU RoHS

China RoHS

Compliant

REACH SVHC

Contains SVHC(2015

June 15): No

Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com

Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

Search Parts in this Series

5556 Series

Application Tooling FAQ	
Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.	
Global	
Description	Product #
FineAdjust™ Applicator for Insulation OD 2.50-2.95mm, 18-24 AWG Wire	0639002600
FineAdjust™ Applicator for Insulation OD 1.65-2.05mm, 18-24 AWG Wire	0639002900
FineAdjust™ Applicator for Insulation OD 1.90-2.30mm - 18-24 AWG	0639015600
FineAdjust™ Applicator for Insulation OD 1.40-1.70mm - 18-24 AWG	0639023900
FineAdjust™ Applicator for Insulation OD	0639024900

2.30-2.60mm - 18-24
AWG
Extraction Tool [0011030044](#)
Hand Crimp Tool for [0638190900](#)
Male and Female
Crimp Terminals,
16-24 AWG Wire
T2 Terminator™ [0639123900](#)
for insulation OD
1.40-1.70mm - 18-24
AWG
T2 Terminator™ [0639124900](#)
for insulation OD
2.30-2.60mm - 18-24
AWG
T2 Terminator™ for [0639102900](#)
insulation OD 1.65
– 2.05mm – 18 – 24
AWG
FineAdjust™ [0639024800](#)
Applicator for
Insulation OD
2.50-2.95mm
Optimized for 18
AWG Only
T2 Terminator™ [0639102600](#)
for insulation OD
2.50-2.95mm - 18-24
AWG
T2 Terminator™ [0639115600](#)
for insulation OD
1.90-2.30mm - 18-24
AWG
T2 Terminator™ [0639124800](#)
for insulation OD
2.50-2.95mm
optimized for 18
AWG only