

TACT
SWITCHESNAVIGATION
SWITCHESPUSHBUTTON
SWITCHESTOGGLE
SWITCHESROCKER
SWITCHESSLIDE
SWITCHESSNAP-ACTION
SWITCHESDIP
SWITCHESKEYLOCK
SWITCHESROTARY
SWITCHESDETECTOR
SWITCHESCAP
OPTIONS

SERIES 400 SWITCHES

ROCKER SWITCHES - SUB-MINIATURE

CUI®
US

FEATURES & BENEFITS

- Variety of switching functions
- Sub-miniature
- Multiple actuator options

APPLICATIONS/MARKETS

- Telecommunications
- Instrumentation
- Test equipment
- Networking
- Computer peripherals

SPECIFICATIONS

Contact Rating:	See contact material options
Life Expectancy:	30,000 make-and-break cycles at full load
Contact Resistance:	20 mΩ max. typical initial @ 2-4 VDC 100 mA for silver and gold plated contacts
Insulation Resistance:	1,000 MΩ min
Dielectric Strength:	1,000 V RMS @ sea level
Operating Temperature:	-30° C to 85° C

MATERIALS

Case:	Diallyl phthalate (DAP) or glass filled nylon, flame retardant, heat stabilized (UL 94-V0)
Rocker:	Nylon
Bushing:	Brass, nickel plated
Housing:	Stainless steel
Terminal/Switch Support:	Brass, or steel tin plated
Contacts / Terminals:	Silver or gold plated copper alloy



HOW TO ORDER

SERIES 400	MODEL NO.	ACTUATOR	ACTUATOR COLOR	TERMINATION	CONTACT MATERIAL	SEAL E
	MSP1 MSP2 MSP3 MSP4 MSP5 MSP6*** MDP1 MDP2 MDP3	R1* R6**	BLK =Black WHT=White RED =Red	M1 M2 M6 M61 M7 M71 VS2 VS21	Q = Silver R = Gold	E = Epoxy Sealed at Base of Terminal



Example Ordering Number

400-MSP1-R6-BLK-M6-R-E

* Std. all models except SPDT with
M6 + M61 terminations.** Std. on SPDT models with
M6 + M61 terminations.


*** Not available with M6 terminations.

Specifications subject to change without notice.

SPDT

2 Comm.
1 3

SCHEMATIC





Model No.	POS 1	POS 2	POS 3
MSP-1	ON	NONE	ON
MSP-2	ON	NONE	(ON)
MSP-3	ON	OFF	ON
MSP-4	(ON)	OFF	(ON)
MSP-5	ON	OFF	(ON)
MSP-6	OFF	NONE	ON
Term. Comm.	2-3	OPEN	2-1

() = Momentary



DPDT




Model No.	POS 1	POS 2	POS 3
MDP-1	ON	NONE	ON
MDP-2	ON	NONE	(ON)
MDP-3	ON	OFF	ON
Term. Comm.	2-3, 5-6	OPEN	2-1, 5-4

() = Momentary


ACTUATOR OPTIONS

R1



Std. all models except SPDT with M6 terminations.

R6



Std. on SPDT models with M6 terminations.


TERMINATION OPTIONS

M1


SOLDER LUG



Single Pole



Double Pole




M2


P.C. MOUNT



Single Pole



Double Pole







TACT
SWITCHESNAVIGATION
SWITCHESPUSHBUTTON
SWITCHESTOGGLE
SWITCHESROCKER
SWITCHESSLIDE
SWITCHESSNAP-ACTION
SWITCHESDIP
SWITCHESKEYLOCK
SWITCHESROTARY
SWITCHESDETECTOR
SWITCHESCAP
OPTIONS

SERIES 400 SWITCHES

ROCKER SWITCHES - SUB-MINIATURE

M6






SPDT



P.C. MOUNTING

M6





DPDT



P.C. MOUNTING

M61





SPDT



P.C. MOUNTING

M61

DPDT



P.C. MOUNTING




TACT
SWITCHESNAVIGATION
SWITCHESPUSHBUTTON
SWITCHESTOGGLE
SWITCHESROCKER
SWITCHESSLIDE
SWITCHESSNAP-ACTION
SWITCHESDIP
SWITCHESKEYLOCK
SWITCHESROTARY
SWITCHESDETECTOR
SWITCHESCAP
OPTIONS

SERIES 400 SWITCHES

ROCKER SWITCHES - SUB-MINIATURE

VS2




SPDT



P.C. MOUNTING

VS2




DPDT



P.C. MOUNTING

VS21

SPDT



P.C. MOUNTING

CONTACT MATERIAL OPTIONS

Q

Fixed Terminal:	Silver plated copper alloy
Moving Contact:	Silver plated copper alloy
Rating:	3 AMPS @ 120 VAC or 28 VDC; 1 AMP @ 250VAC

R

Fixed Terminal:	Copper alloy with gold plate over nickel plate
Moving Contact:	Copper alloy with gold plate over nickel plate
Rating:	0.4 VA max. @ 20 VAC or DC max.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

E-Switch:

[400MDP1R1M7QE](#) [400MSP1R1BLKVS2QE](#) [400MSP1R1REDVS2QE](#) [400MDP2R1BLKM6QE](#)
[400MDP3R1BLKM6QE](#) [400MSP5R1BLKVS2RE](#) [400MSP1R1BLKM7RE](#) [400MSP1R6BLKM71QE](#)
[400MDP1R1BLKM6QE](#) [400MDP1R1BLKM2QE](#) [400MDP1R1BLKM61QE](#) [400MDP1R1BLKM7QE](#) [400MDP1R1M1QE](#)
[400MDP1R1REDM7QE](#) [400MDP1R1VS2QE](#) [400MDP1R6BLKM6RE](#) [400MDP1R6BLKVS2RE](#) [400MDP1R6M6QE](#)
[400MDP2R1BLKM2QE](#) [400MDP2R6BLKM7QE](#) [400MDP3R1BLKM1QE](#) [400MDP3R1BLKM2QE](#)
[400MDP3R6WHTM1QE](#) [400MSP1R1BLKM1QE](#) [400MSP1R1BLKM1RE](#) [400MSP1R1BLKM2RE](#)
[400MSP1R1BLKM6QE](#) [400MSP1R1BLKM6RE](#) [400MSP1R1BLKM7QE](#) [400MSP1R1BLKVS2RE](#)
[400MSP1R6BLKM1RE](#) [400MSP1R6BLKM61QE](#) [400MSP1R6BLKM6QE](#) [400MSP1R6BLKM6RE](#)
[400MSP1R6BLKM7QE](#) [400MSP1R6BLKM7RE](#) [400MSP1R6BLKVS2QE](#) [400MSP1R6BLKVS2RE](#)
[400MSP1R6WHTM6QE](#) [400MSP2R6BLKM2RE](#) [400MSP3R1BLKM1RE](#) [400MSP3R1BLKM2QE](#)
[400MSP3R1BLKM7QE](#) [400MSP3R1REDM7QE](#) [400MSP3R1VS2QE](#) [400MSP3R6BLKM6QE](#) [400MSP3R6BLKM6RE](#)
[400MSP4R1BLKM2RE](#) [400MSP4R1BLKM7QE](#) [400MSP4R6BLKM1QE](#) [400MSP4R6BLKM6RE](#)
[400MSP5R1BLKM1QE](#) [400MDP1R1M6RE](#) [400MDP1R1VS2RE](#) [400MDP3R1WHTM1QE](#) [400MDP3R6BLKM7QE](#)
[400MSP1R1BLKM71QE](#) [400MSP1R1M6QE](#) [400MSP1R1REDM1RE](#) [400MSP1R6M2QE](#) [400MSP1R6REDM6QE](#)
[400MSP1R6WHTM6RE](#) [400MSP2R6BLKM6QE](#) [400MSP3R1BLKM2RE](#) [400MSP4R1BLKM1QE](#)
[400MSP4R1BLKM1RE](#) [400MSP4R1BLKM2QE](#) [400MSP4R1BLKM71QE](#) [400MSP4R6BLKVS21RE](#)
[400MDP1R6BLKM7QE](#) [400MSP1R6BLKM1QE](#) [400MSP5R1BLKM71QE](#) [400MSP1R6BLKM71RE](#)
[400BWMSP1R2BLKSM6RE](#)