



Technical specification:

Rated voltage: IEC 61076-2-101	4pos 160 V
Current rating: IEC 61076-2-101	4 A at 40°C
Insulation resistance: IEC 60512	≥100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	≥100

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	PA, UL 94
Sealing:	FPM
Coupling nut:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

Installation specification:

Recommended torque:	0,6 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 13: 36-000220

Contact assignment:

1)	brown
2)	white
3)	blue
4)	black
Shielding coupling nut	

Part no:	Description:	Length L:	Cable:
43-12419	SAL - 12S - RKW4 - 2 / G2	2m	TPU, UL 20549, black, 4x0,34mm ² Cable: 781-G23400
43-12420	SAL - 12S - RKW4 - 3 / G2	3m	
43-12421	SAL - 12S - RKW4 - 5 / G2	5m	
43-12422	SAL - 12S - RKW4 - 10 / G2	10m	
43-xxxxx	SAL - 12S - RKW4 - ... / G2	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND	Directive 2002/95/EC RoHS compliant	Index: a 09.03.11 VF Ä3767 Coupling nut modified, spanner flats added, data sheet modified		title: Female connector M12x1 angled, 360°-shielding									
		tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%			<table border="1"> <tr> <td></td> <td>date</td> <td>name</td> </tr> <tr> <td>drawn</td> <td>13.10.08</td> <td>Mankopf</td> </tr> <tr> <td>appd.</td> <td>13.10.08</td> <td>Fromm</td> </tr> </table>		date	name	drawn	13.10.08	Mankopf	appd.	13.10.08
			date		name								
		drawn	13.10.08		Mankopf								
appd.	13.10.08	Fromm											
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			dwg no: 43K1A755										
			part no: see table										