

This document was generated on 07/26/2016

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0436500225

Status: Active

Overview: Micro-Fit 3.0<sup>TM</sup> Connectors

Description: Micro-Fit 3.0™ Vertical Header, 3.00mm Pitch, Single Row, 2 Circuits, with Solder Tab,

Gold, Glow Wire Capable, Black

**Documents:** 

3D Model RoHS Certificate of Compliance (PDF)

<u>Drawing (PDF)</u> <u>Product Literature (PDF)</u>

Product Specification PS-43650 (PDF)

## **Agency Certification**

CSA LR19980 UL E29179

General

Product Family PCB Headers

Series <u>43650</u>

Application Power, Wire-to-Board Comments "High Temperature|So

"High Temperature|Square Pin|Solder Type<P><P>This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <P><P> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <P> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for

possible product options."
Micro-Fit 3.0™ Connectors

Overview <u>Micro-Fit 3.0™ Connector</u>

Product Literature Order No 987650-5984
Product Name Micro-Fit  $3.0^{\text{TM}}$ UPC 800754780773

**Physical** 

Breakaway No Circuits (Loaded) 2 Circuits (maximum) 2 Color - Resin **Black** Durability (mating cycles max) 30 Flammability 94V-0 Glow-Wire Compliant Yes Mated Height 17.27mm

Material - Metal Brass
Material - Plating Mating Gold
Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

Net Weight 0.657/g



## Series image - Reference only

## **EU ELV**

**Not Relevant** 

EU RoHS China RoHS

Compliant

**REACH SVHC** 

Not Contained Per - ED/21/2016 (20 June

2016)

**Halogen-Free** 

**Status** 

Low-Halogen

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS ELV Green Image Not Relevant

Search Parts in this Series

43650 Series

**Mates With** 

43645 Micro-Fit 3.0™ Receptacle Housing

Number of Rows1OrientationVerticalPCB LocatorYesPCB RetentionYesPCB Thickness - Recommended1.60mm

Packaging Type Embossed Tape on Reel

 $\begin{array}{lll} \text{Pitch - Mating Interface} & 3.00\text{mm} \\ \text{Plating min - Mating} & 0.381\mu\text{m} \\ \text{Plating min - Termination} & 2.540\mu\text{m} \\ \text{Polarized to PCB} & \text{Yes} \\ \text{Shrouded} & \text{Fully} \\ \text{Stackable} & \text{No} \\ \end{array}$ 

Temperature Range - Operating -40°C to +105°C Termination Interface: Style Surface Mount

**Electrical** 

Current - Maximum per Contact 5.0A Voltage - Maximum 600V

**Solder Process Data** 

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

003

Process Temperature max. C

260

**Material Info** 

**Reference - Drawing Numbers** 

Product Specification PS-43650
Sales Drawing SD-43650-009

This document was generated on 07/26/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION