


SPECIFICATION CONTROL DRAWING				SCD		44A013X				
Title		THREE CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, GENERAL PURPOSE, 600 VOLT			Date		11-3-15	Revision		E
This specification sheet forms a part of the latest issue of Raychem Specification 44.										
COMPONENT WIRES - 44A011X 										
CABLE CONSTRUCTION DETAILS										
PART NUMBER 1/	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)						
		NOMINAL	MAXIMUM							
44A013X-26-*	26	.073	.078	4.3						
44A013X-24-*	24	.086	.091	6.4						
44A013X-22-*	22	.102	.106	9.5						
44A013X-20-*	20	.119	.123	14.1						
44A013X-18-*	18	.140	.145	21.4						
44A013X-16-*	16	.156	.162	27.2						
44A013X-14-*	14	.192	.199	42.5						
44A013X-12-*	12	.233	.239	66.4						
CABLE RATINGS AND ADDITIONAL REQUIREMENTS										
TEMPERATURE RATING: 150°C Maximum continuous conductor temperature VOLTAGE RATING: 600 volts (rms) at sea level DIELECTRIC WITHSTAND: 2500 volts (rms), 60 Hz, 1 minute INSULATION FLAWS: Spark Test, 5.7 kV (rms) at 3 kHz Impulse Dielectric Test, 8.0 kV (peak)					1/ PART NUMBER: The "X" in the part numbers above shall be replaced with a conductor material designator as follows: 1 tin-coated copper 2 silver-coated copper 3 nickel-coated copper 4 silver-coated high-strength copper alloy (AWG 26-16 only) The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors. Colors shown do not necessarily reflect the sequence of manufacturing. Example: AWG 20, tin-coated copper conductors; black, brown, and red component wires: 44A0131-20-0/1/2					
NOTE: Nominal values are for information only. Nominal values are not requirements.										
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.										
1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.										
Page 1 of 1	Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.				 Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297					
	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL									
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.									