

RS Part Number: **466273**

Europa Part Number: **LBDI253P**

Specifications and dimensions

- Rotary Isolator For Din Rail Mount
- Complete With Shaft and Handle
- Din Rail Mount Switch



Dimensions	
Height	87mm
Width	68mm
Depth	56mm
Handle:	
Height	64mm
Width	64mm
Depth	42mm
Shaft:	
Length	282mm
Weight	0.265Kg
Features	
Rated operational voltage Ue IEC &EN	690V
Rated operational voltage Ue UL	600V
Rated impulse withstand voltage Uimp	6kV
Rated uninterrupted current Iu	25A
Rated operational current Ie AC22A	25A
Rated operational current Ie AC21A	32A
Rated operational current Ie AC1	32A
Rated operational power AC23A (50/60Hz) 230V	11kW
Rated operational power AC23A (50/60Hz) 415V	15kW
Rated operational power AC23A (50/60Hz) 690V	22kW
Rated operational power AC3 (50/60Hz) 230V	7.5kW
Rated operational power AC3 (50/60Hz) 415V	11kW
Rated operational power AC3 (50/60Hz) 690V	15kW
UL power rating 3 phase DOL 110V	3hp
UL power rating 3 phase DOL 230V	7.5hp
UL power rating 3 phase DOL 480V	15hp
UL power rating 3 phase DOL 600V	20hp
UL power rating 1 phase DOL 110V	1.5hp
UL power rating 1 phase DOL 230V	2hp
UL short circuit fuse rating class J	45A
UL rated fused short circuit current	10kA
IEC short circuit capacity max fuse size GI	32A
IEC rated fused short circuit current	30kA
Maximum terminal capacity	10mm ²
Recommended tightening torque	1.7Nm
Related Products	
Neutral contact early make/late break	LB263AUXEM
Volt free contact 1NC + 1NO	LBAC16RM
Volt free contact 2NO	LBAC16RM2NO
Main pole contact	LB263MAINPOLE
Extended main pole + 1NC/1NO auxilliary	LB263ERMC
Extended neutral + 1NC/1NO auxilliary	LB263ERNCC
Gasket to provide IP65 rating	LBGASKET