Data & Signal, Plug, 2.5 mm, 2-pole, solder terminal, shielded







Description

- Solder terminal: for cable mounting
- Data and Signal transfer
- Data and Signal Connectors 2-pole, shielded, straight

References

Alternative: Housing insulated 4801.1210

Weblinks


pdf-datasheet, html-datasheet, General Product Information, RoHS, CHINA-RoHS, REACH, Mating Connectors, e-Shop, SCHURTER-Stock-Check, Distributor-Stock-Check

Technical Data

Diameter	2.5 mm		
Number of Poles	2-pole		
Ratings DC	1 A / 12 VDC		
Ratings AC	0.65 A / 12 VAC		
Dielectric Strength	500 VDC		
Insulation Resistance	> 10000 MΩ @ 500 VDC		

Allowable Operation Temp.	-20°C to 70°C
Terminal	solder terminal
Housing	screened
Style	straight
Lifetime	10000 Insertions

Dimensions



All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Data and Signal Plug/ Sockets	2.5	2-pole	solder terminal	4801.1200

Most Popular.

Availability for all products can be searched real-time:http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit 100 Pcs

Mating Outlets/Connectors

Category / Description



Data and Signal Plug/Socket Overview complete

Daten & Signal, Socket, 2.5 mm, 2-pole, solder terminal, shielded

4801.2200

Data and Signal Plug/Socket further types to 4801 UK-Stecker, D=2,5mm

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schurter: 4801.1200